



Main

Range	Prisma
Range compatibility	Prisma P
Product or component type	Mounting plate
Accessory / separate part category	Installation accessory
Installed device	<p>Compact : fixed NSX400 without earth leakage protection - control: direct front rotary handle - horizontal installation</p> <p>Compact : fixed NSX630 without earth leakage protection - control: direct front rotary handle - horizontal installation</p> <p>Compact : fixed NSX400 with earth leakage protection - control: direct front rotary handle - horizontal installation</p> <p>Compact : fixed NSX630 with earth leakage protection - control: direct front rotary handle - horizontal installation</p> <p>Easypact : fixed CVS400 without earth leakage protection - control: direct front rotary handle - horizontal installation</p> <p>Easypact : fixed CVS630 without earth leakage protection - control: direct front rotary handle - horizontal installation</p> <p>Easypact : fixed CVS400 with earth leakage protection - control: direct front rotary handle - horizontal installation</p> <p>Easypact : fixed CVS630 with earth leakage protection - control: direct front rotary handle - horizontal installation</p> <p>Compact : fixed NSX400 without earth leakage protection - control: motor mechanism - horizontal installation</p> <p>Compact : fixed NSX630 without earth leakage protection - control: motor mechanism - horizontal installation</p> <p>Compact : fixed NSX400 with earth leakage protection - control: motor mechanism - horizontal installation</p> <p>Compact : fixed NSX630 with earth leakage protection - control: motor mechanism - horizontal installation</p> <p>Compact : plug-in NSX400 without earth leakage protection - control: direct front rotary handle - horizontal installation</p> <p>Compact : plug-in NSX630 without earth leakage protection - control: direct front rotary handle - horizontal installation</p> <p>Compact : plug-in NSX400 with earth leakage protection - control: direct front rotary handle - horizontal installation</p> <p>Compact : plug-in NSX630 with earth leakage protection - control: direct front rotary handle - horizontal installation</p> <p>Compact : plug-in NSX400 without earth leakage protection - control: motor mechanism - horizontal installation</p>

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

	Compact : plug-in NSX630 without earth leakage protection - control: motor mechanism - horizontal installation
	Compact : plug-in NSX400 with earth leakage protection - control: motor mechanism - horizontal installation
	Compact : plug-in NSX630 with earth leakage protection - control: motor mechanism - horizontal installation
	Compact : plug-in NSX400 without earth leakage protection - control: toggle - horizontal installation
	Compact : plug-in NSX630 without earth leakage protection - control: toggle - horizontal installation
	Compact : plug-in NSX400 with earth leakage protection - control: toggle - horizontal installation
	Compact : plug-in NSX630 with earth leakage protection - control: toggle - horizontal installation
Poles description	1 x 4P : fixed : NSX400 horizontal installation 1 x 4P : fixed : NSX630 horizontal installation 1 x 4P : fixed : CVS400 horizontal installation 1 x 4P : fixed : CVS630 horizontal installation 1 x 4P : plug-in : NSX400 horizontal installation 1 x 4P : plug-in : NSX630 horizontal installation

## Complementary

Installation description	Cubicle - width 650 mm, depth 400 mm
Number of vertical modules [50 mm]	4 module(s) : NSX400 without earth leakage protection , direct in 650 mm Wide cubicle 4 module(s) : NSX630 without earth leakage protection , direct in 650 mm Wide cubicle 4 module(s) : NSX400 with earth leakage protection , direct in 650 mm Wide cubicle 4 module(s) : NSX630 with earth leakage protection , direct in 650 mm Wide cubicle 5 module(s) : CVS400 without earth leakage protection , direct in 650 mm Wide cubicle 5 module(s) : CVS630 without earth leakage protection , direct in 650 mm Wide cubicle 5 module(s) : NSX400 without earth leakage protection , direct in 650 mm Wide cubicle 5 module(s) : NSX630 without earth leakage protection , direct in 650 mm Wide cubicle 5 module(s) : CVS400 with earth leakage protection , direct in 650 mm Wide cubicle 5 module(s) : CVS630 with earth leakage protection , direct in 650 mm Wide cubicle 5 module(s) : NSX400 with earth leakage protection , direct in 650 mm Wide cubicle 5 module(s) : NSX630 with earth leakage protection , direct in 650 mm Wide cubicle
Height	250 mm
Product weight	2.96 kg
Surface finish	Smooth Matt
Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Colour	White RAL 9001

## Environment

Standards	IEC 61439-2
Product certifications	ASEFA

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0807 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available <a href="#">Product Environmental Profile</a>
Product end of life instructions	Available <a href="#">End of Life Information</a>

## Contractual warranty

Warranty period	18 months
-----------------	-----------