


Product data sheet

Specifications



Mounting Plate Vert. Withd. NS-MTZ1/NT 3P 1600A W400 Prisma P

03488

 **Discontinued on:** Apr 25, 2023

 **Discontinued**

Main

Range	Prisma
Range Of Product	Prisma P
Product Or Component Type	Mounting plate
Accessory / Separate Part Category	Installation accessory
Range Compatibility	Prisma Prisma P cubicle
Installation Description	Cubicle - width 400 mm depth 400 mm
Installed Device	ComPact: drawout NS1250 - control: toggle - vertical installation ComPact: drawout NS1250 - control: direct front rotary handle - vertical installation ComPact: drawout NS1250 - control: motor mechanism - vertical installation ComPact: drawout NS1600 - control: toggle - vertical installation ComPact: drawout NS1600 - control: direct front rotary handle - vertical installation ComPact: drawout NS1600 - control: motor mechanism - vertical installation ComPact: drawout NS630b...1000 - control: toggle - vertical installation ComPact: drawout NS630b...1000 - control: direct front rotary handle - vertical installation ComPact: drawout NS630b...1000 - control: motor mechanism - vertical installation Masterpact: drawout NT06...10 - control: toggle - vertical installation Masterpact: drawout NT12 - control: toggle - vertical installation Masterpact: drawout NT16 - control: toggle - vertical installation
Poles Description	1 x 3P: drawout NS1250 vertical installation 1 x 3P: drawout NS1600 vertical installation 1 x 3P: drawout NS630b...1000 vertical installation 1 x 3P: drawout NT06...10 vertical installation 1 x 3P: drawout NT12 vertical installation 1 x 3P: drawout NT16 vertical installation
Number Of Vertical Modules [50 Mm]	36 module(s): NS1250, direct in 400 mm Widecubicle 36 module(s): NS1600, direct in 400 mm Widecubicle 36 module(s): NS630b...1000, direct in 400 mm Widecubicle 36 module(s): NT06...10, front connection in 400 mm Widecubicle 36 module(s): NT12, front connection in 400 mm Widecubicle 36 module(s): NT16, front connection in 400 mm Widecubicle
Standards	IEC 61439-2
Product Certifications	ASEFA

Complementary

Protective Treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Surface Finish	Matt Smooth
Colour	White (RAL 9001)
Width	400 mm
Height	30 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Net Weight	1.62 kg
Functional Unit	400 mm 400 mm Prisma P cubicle ComPact NS1250 drawout toggle vertical 3P 1 direct 36 1062.5 mm 400 mm 400 mm Prisma P cubicle ComPact NS1250 drawout direct front rotary handle vertical 3P 1 direct 36 1062.5 mm 400 mm 400 mm Prisma P cubicle ComPact NS1250 drawout motor mechanism vertical 3P 1 direct 36 1062.5 mm 400 mm 400 mm Prisma P cubicle ComPact NS1600 drawout toggle vertical 3P 1 direct 36 1062.5 mm 400 mm 400 mm Prisma P cubicle ComPact NS1600 drawout direct front rotary handle vertical 3P 1 direct 36 1062.5 mm 400 mm 400 mm Prisma P cubicle ComPact NS1600 drawout motor mechanism vertical 3P 1 direct 36 1062.5 mm 400 mm 400 mm Prisma P cubicle ComPact NS630b...1000 drawout toggle vertical 3P 1 direct 36 1062.5 mm 400 mm 400 mm Prisma P cubicle ComPact NS630b...1000 drawout direct front rotary handle vertical 3P 1 direct 36 1062.5 mm 400 mm 400 mm Prisma P cubicle ComPact NS630b...1000 drawout motor mechanism vertical 3P 1 direct 36 1062.5 mm 400 mm 400 mm Prisma P cubicle Masterpact NT06...10 drawout toggle vertical 3P 1 front connection 36 1062.5 mm 400 mm 400 mm Prisma P cubicle Masterpact NT12 drawout toggle vertical 3P 1 front connection 36 1062.5 mm 400 mm 400 mm Prisma P cubicle Masterpact NT16 drawout toggle vertical 3P 1 front connection 36 1062.5 mm

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.0 cm
Package 1 Width	33.0 cm
Package 1 Length	36.5 cm
Package 1 Weight	1.62 kg
Unit Type Of Package 2	S04
Number Of Units In Package 2	10
Package 2 Height	30.0 cm
Package 2 Width	40.0 cm
Package 2 Length	60.0 cm
Package 2 Weight	17.0 kg

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance



Mercury Free



RoHS Exemption Information

[Yes](#)



Halogen Free Plastic Parts Product

Certifications & Standards

Eu RoHS Directive

Pro-active compliance (Product out of EU RoHS legal scope)

[EU RoHS Declaration](#)

China RoHS Regulation

[China RoHS declaration](#)

Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure

[Product Environmental Profile](#)

Circularity Profile

[End of Life Information](#)