



Main

Range	Prisma
Range compatibility	Prisma P
Product or component type	Mounting plate
Accessory / separate part category	Installation accessory
Installed device	Compact : drawout NS630b...1000 - control: direct front rotary handle - vertical installation Compact : drawout NS1250 - control: direct front rotary handle - vertical installation Compact : drawout NS1600 - control: direct front rotary handle - vertical installation Compact : drawout NS630b...1000 - control: motor mechanism - vertical installation Compact : drawout NS1250 - control: motor mechanism - vertical installation Compact : drawout NS1600 - control: motor mechanism - vertical installation Compact : drawout NS630b...1000 - control: toggle - vertical installation Compact : drawout NS1250 - control: toggle - vertical installation Compact : drawout NS1600 - control: toggle - vertical installation Masterpact : drawout NT06...10 - control: toggle - vertical installation Masterpact : drawout NT12 - control: toggle - vertical installation Masterpact : drawout NT16 - control: toggle - vertical installation
Poles description	1 x 3P : drawout : NS630b...1000 vertical installation 1 x 3P : drawout : NS1250 vertical installation 1 x 3P : drawout : NS1600 vertical installation 1 x 3P : drawout : NT06...10 vertical installation 1 x 3P : drawout : NT12 vertical installation 1 x 3P : drawout : NT16 vertical installation

Complementary

Installation description	Cubicle - width 400 mm, depth 400 mm
Number of vertical modules [50 mm]	36 module(s) : NS1250, direct in 400 mm Wide cubicle 36 module(s) : NS1600, direct in 400 mm Wide cubicle 36 module(s) : NS630b...1000, direct in 400 mm Wide cubicle 36 module(s) : NT06...10, front connection in 400 mm Wide cubicle 36 module(s) : NT12, front connection in 400 mm Wide cubicle 36 module(s) : NT16, front connection in 400 mm Wide cubicle
Height	30 mm
Product weight	1.62 kg
Surface finish	Matt

	Smooth
Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Colour	White RAL 9001

Environment

Standards	IEC 61439-2
Product certifications	ASEFA

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0807 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available Product Environmental Profile
Product end of life instructions	Available End of Life Information

Contractual warranty

Warranty period	18 months
-----------------	-----------