

Product data sheet

Specifications

LINERGY FM 4P DIS.BLOCK 200A 36M 81HOLES



04026

 **Discontinued on:** Apr 25, 2023

 **Discontinued**

Main

Range	Linergy
Range Of Product	Linergy
Product Or Component Type	Device feeder
Product Name	Linergy FM
Range Compatibility	Prisma Prisma G enclosure Prisma Prisma P enclosure Spacial Spacial SFP enclosure
Product Compatibility	Spacial enclosures
Ip Degree Of Protection	IPxx B

Complementary

Installed Device	modular device
Poles Description	3P + N
[Ue] Rated Operational Voltage	690 V AC
[Ui] Rated Insulation Voltage	750 V AC 50/60 Hz
[Uimp] Rated Impulse Withstand Voltage	8 kV
[Ie] Rated Operational Current	200 A
[In] Rated Current	200 A at 40 °C
[Ipk] Rated Peak Withstand Current	20 kA
I²T On Activation	6700000 A².s
Connections - Terminals	Supply: crimped lug50 mm² Supply: flexible bars, 20 x 3 mm Distribution: quick-connect terminal strips (phase) , 18 x 4...10 mm² (flexible) Distribution: quick-connect terminal strips (phase) , 18 x 4...10 mm² (rigid) Distribution: quick-connect terminal strips (neutral) , 27 x 4...10 mm² (flexible) Distribution: quick-connect terminal strips (neutral) , 27 x 4...10 mm² (rigid)
9 Mm Pitches	72
Total Number Of 18 Mm Modules	36
Width	750 mm
Net Weight	2.3 kg
Colour	Anthracite grey (RAL 7016)

Environment

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Standards	IEC 61439-1, inside Prisma IEC 61439-2, inside Prisma IEC 60947-7-1
-----------	---

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	7.0 cm
Package 1 Width	7.6 cm
Package 1 Length	66.0 cm
Package 1 Weight	2.3 kg
Unit Type Of Package 2	BB1
Number Of Units In Package 2	3
Package 2 Height	6.5 cm
Package 2 Width	23.0 cm
Package 2 Length	66.0 cm
Package 2 Weight	7.6 kg
Unit Type Of Package 3	P06
Number Of Units In Package 3	90
Package 3 Height	117.0 cm
Package 3 Width	80.0 cm
Package 3 Length	60.0 cm
Package 3 Weight	235.0 kg

Contractual warranty

Warranty	18 months
----------	-----------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

✓ Reach Free Of Svhc

✓ Toxic Heavy Metal Free

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

✓ Halogen Free Product

Certifications & Standards

Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins