Specifications



CU CONNECTIONS 125A 4P W230 WITH 35² FERRULE+45[°] ANGLE LUG

04145

(Discontinued on: Dec 15, 2021

① Discontinued

Main

mann	
Range	Linergy
Range Of Product	Linergy
Product Or Component Type	Connection
Product Name	Linergy BW
Product Name	Prisma Prisma P enclosure Prisma Prisma G enclosure Linergy Linergy BW busbar
Standards	IEC 61439-1, inside Prisma IEC 61439-2, inside Prisma
Product Certifications	ASEFA

Complementary

Complemental y		
Cubicle-Device Connection	Linergy BS busbar Linergy FH comb busbar	
Poles Description	4P	
Installation Description	Cubicle - width 650mm Floor-standing enclosure - width 600mm Wall-mounted enclosure - width 600mm Floor-standing enclosure - width 850mm Pack enclosure - width 550mm	
Installed Device	Multi9: NG125 ComPact: INS125	
[le] Rated Operational Current	125 A	
[In] Rated Current	125 A	
Length	230 mm	
Net Weight	0.42 kg	
Quantity Per Set	Set of 4	

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Eq

Well-being performance

Reach Free Of Svhc
Toxic Heavy Metal Free
Mercury Free
Rohs Exemption Information Yes
Halogen Free Plastic Parts Product

Certifications & Standards

Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile