



### Main

Range	Prisma
Product name	Pack 160
IP degree of protection	IP30 with door IP30 without door IP31 with door and canopy IP43 with door, canopy and IP43 gasket
Product or component type	Enclosure extension
Enclosure type	Empty enclosure
Enclosure mounting	Surface Flush with kit
Type of front plate	Without (to be ordered separately)
Number of vertical modules [50 mm]	9
Number of 18 mm modules per row	24

### Complementary

Installation description	Pack enclosure - width 555 mm
[Ui] rated insulation voltage	750 V
[In] rated current	160 A at 40 °C conforming to IEC 61439-2
Number of horizontal rows	3
Enclosure material	Enclosure : treated sheet steel
Quantity per set	Set of 1
Height	480 mm
Width	555 mm
Depth	157 mm
Product weight	8.72 kg
Surface finish	Matt Smooth
Colour	White RAL 9001

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Environment

IK degree of protection	IK07 without door conforming to EN/IEC 62262 IK08 with door
Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Standards	IEC 62208 IEC 61439-2 IEC 61439-1 IEC 61439-3

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0832 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available <a href="#">Product Environmental Profile</a>
Product end of life instructions	Need no specific recycling operations

## Contractual warranty

Warranty period	18 months
-----------------	-----------

## 08013 is replaced by:



### Mounting accessories NSYAMPA2924TB

Insulating mounting plate, thickness 25 mm, For boxes of H275W225 mm

Qty 1

Reason for Substitution: Rebranding | Substitution date: 31 October 2009 | -