

Closing voltage release MX, Compact NS100/NS630, 220/240VAC

29843

Main

Device Short Name	MX
Product Or Component Type	Voltage release
Device Application	Control
Voltage Release Type	Shunt trip release
[Uc] Control Circuit Voltage	220240 V AC 60 Hz

Packing Units

PCE
1
6.3 cm
4.0 cm
8.0 cm
127.0 g
BB1
10
9.0 cm
14.5 cm
22.5 cm
1.337 kg
S03
60
30.0 cm
30.0 cm
40.0 cm
8.509 kg

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information