
Specifications



low level auxiliary contact, ComPact NS630b to NS1600, drawout, circuit breaker status OF, 1 changeover contact type

33804

Main

| Product Or Component Type | Auxiliary contact |
|-----------------------------|----------------------------|
| Device Short Name | OF |
| Device Application | Breaker status monitoring |
| Range Compatibility | ComPact ComPact NS630b1600 |
| Signal Contacts Composition | 1 NO/NC |

Complementary

| Local Signalling | ON/OFF indication for open/close |
|--|---------------------------------------|
| Auxiliary Contacts Type | Low level |
| Mounting Mode | Clip-on |
| [Ith] Conventional Free Air Thermal Current | 5 A |
| Breaking Capacity (A) | AC-12: 5 A at 24 V AC 50/60 Hz |
| | AC-12: 5 A at 48 V AC 50/60 Hz |
| | AC-12: 5 A at 110 V AC 50/60 Hz |
| | AC-12: 5 A at 220/240 V AC 50/60 Hz |
| | AC-12: 5 A at 380/440 V AC 50/60 Hz |
| | AC-12: 5 A at 480 V AC 50/60 Hz |
| | AC-15: 3 A at 24 V AC 50/60 Hz |
| | AC-15: 3 A at 48 V AC 50/60 Hz |
| | AC-15: 2.5 A at 110 V AC 50/60 Hz |
| | AC-15: 2 A at 220/240 V AC 50/60 Hz |
| | AC-15: 1.5 A at 380/440 V AC 50/60 Hz |
| | AC-15: 1 A at 480 V AC 50/60 Hz |
| | DC-12: 5 A at 24 V DC 50/60 Hz |
| | DC-12: 2.5 A at 48 V DC 50/60 Hz |
| | DC-12: 0.6 A at 110 V DC |
| | DC-12: 0.3 A at 250 V DC |
| | DC-14: 1 A at 24 V DC |
| | DC-14: 0.2 A at 48 V DC |
| | DC-14: 0.05 A at 110 V DC |
| | DC-14: 0.03 A at 250 V DC |
| Minimum Load | 1 mA at 4 V DC |
| Accessory / Separate Part | Spare part for Compact NS630b 1600 |

Accessory / Separate Part Category Spare part for Compact NS630b...1600

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|---------|
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 2.0 cm |
| Package 1 Width | 5.0 cm |
| Package 1 Length | 15.0 cm |
| Package 1 Weight | 88.0 g |

Contractual warranty

Warranty

18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance

| Reach Free Of Svhc | |
|----------------------------|---|
| V Toxic Heavy Metal Free | |
| Mercury Free | |
| Rohs Exemption Information | Yes |
| Vvc Free | |
| | |
| Reach Regulation | REACh Declaration |
| Eu Rohs Directive | Compliant |
| | EU RoHS Declaration |
| China Rohs Regulation | China RoHS declaration |
| | Pro-active China RoHS declaration (out of China RoHS legal scope) |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |