Specifications



① Discontinued

Wibe - tele-conduit 36/50 - 2 m - stainless steel AISI 316L

725590

() Discontinued on: Jan 3, 2022

Important message: This product belongs to Cable Support which is no longer commercialized by Schneider Electric. As per the first of January 2022 the commercialization is managed by Wibe-Group, Please follow the link www.wibe-group.com for further details.

Main

Range	Wibe
Range Of Product	Wibe Cable Ladders
Product Or Component Type	Tele-conduit
Device Short Name	36
Mounting Location	Area with almost permanent high levels of humidity, airborne pollution and salt purify- ing plants and offshore

Complementary

Product Destination	Cable ladder
Cable Entry	Knock-out
Material With Surface Treatment	Stainless steel AISI 316L
Corrosion Class	С5-М
Height	24 mm
Width	50 mm
Length	2000 mm
Net Weight	94 kg / set of 100

Packing Units

•	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	2.4 cm
Package 1 Width	5 cm
Package 1 Length	200 cm
Package 1 Weight	940 g

Contractual warranty

Warranty

18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Eq

Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc
Toxic Heavy Metal Free

Mercury Free

Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations