Specifications



(!) Discontinued

Wibe - Cable tray W1-100 - 2m unperforated - steel pre-galvanized White 30

728987

Uiscontinued on: Jan 3, 2022

Important message: This product belongs to Cable Support which is no longer commercialized by Schneider Electric. As per the first of January 2022 the commercialization is managed by Wibe-Group, Please follow the link www.wibe-group.com for further details.

Main

Range	Wibe
Range Of Product	Wibe Cable Trays
Product Or Component Type	Cable tray
Device Short Name	W1
Mounting Location	Partly outdoor environment with low exposure to corrosion ware-houses and parking garages

Complementary

Cable Tray Type	Unperforated
Material With Surface Treatment	Steel, pre-galvanized white
Corrosion Class	C2
Hole Size	Ø 5.8 mm tray ends for locking of joints
Height	40 mm
Width	100 mm
Length	2 m
Net Weight	115 kg / 100 m

Packing Units

-	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	4 cm
Package 1 Width	9.8 cm
Package 1 Length	200 cm
Package 1 Weight	2.4 kg

Contractual warranty

Warranty

18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Eq

Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc
Toxic Heavy Metal Free

Mercury Free

Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations