

Wibe - install. tray W4-200 - 1.96m perforated - steel pre-galvanized white

736637

Discontinued on: Jan 3, 2022

! Discontinued

Important message: This product belongs to Cable Support which is no longer commercialized by Schneider Electric. As per the first of January 2022 the commercialization is managed by Wibe-Group, Please follow the link www.wibe-group.com for further details.

Main

Range	Wibe	
Range Of Product	Wibe Cable Trays	
Product Or Component Type	Installation tray	
Device Short Name	W4	
Mounting Location	Partly outdoor environment with low exposure to corrosion ware-houses and parking	

Complementary

Cable Tray Type	Perforated
Material With Surface Treatment	Steel, pre-galvanized white
Corrosion Class	C2
Height	15 mm
Width	200 mm
Length	1960 mm
Net Weight	195 kg / 100 m

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	1.5 cm
Package 1 Width	20 cm
Package 1 Length	196 cm
Package 1 Weight	3.57 kg

Contractual warranty

Warranty 18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

✓ Reach Free Of Svhc
 ✓ Toxic Heavy Metal Free
 ✓ Mercury Free
 ✓ Rohs Exemption Information

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations