

Wibe - side joint W49/60 - steel pregalvanized

782267

! Discontinued on: Jan 3, 2022



Important message: This product belongs to Cable Support which is no longer commercialized by Schneider Electric. As per the first of January 2022 the commercialization is managed by Wibe-Group, Please follow the link www.wibe-group.com for further details.

Main

Range	Wibe
Range Of Product	Wibe Cable Trays
Product Or Component Type	Side joint
Device Short Name	W49
Mounting Location	Partly outdoor environment with low exposure to corrosion ware-houses and parking garages

Complementary

Product Destination	Reinforced cable tray H= 60 mm	
Mounting Mode	Push-in	
Fixing Mode	By bolt	
Material With Surface Treatment	Steel, pre-galvanized	
Corrosion Class	C2	
Height	58 mm	
Width	300 mm	
Net Weight	27 kg / set of 100	

Packing Units

Unit Type Of Package 1	PCE
	1 02
Number Of Units In Package 1	1
Package 1 Height	0.2 cm
Package 1 Width	5.8 cm
Package 1 Length	30 cm
Package 1 Weight	270 g

Contractual warranty

Warranty 18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

⊘	Reach Free Of Svhc	
⊘	Toxic Heavy Metal Free	
⊘	Mercury Free	
②	Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations