Specifications



#### (!) Discontinued

Wibe - support bracket W19/60-400 - steel pre-galvanized

782335

() Discontinued on: Jan 3, 2022

Important message: This product belongs to Cable Support which is no longer commercialized by Schneider Electric. As per the first of January 2022 the commercialization is managed by Wibe-Group, Please follow the link www.wibe-group.com for further details.

#### Main

Range	Wibe
Product Or Component Type	Support bracket
Range Compatibility	Wibe
Environmental Characteristic	Partly outdoor environment with low exposure to corrosion ware-houses and parking garages

# Complementary

Mounting Location	Inside cable ladder	
Material With Surface Treatment	Steel, pre-galvanized	
Corrosion Class	C2	
Width	389 mm	
Net Weight	77 kg / set of 100	

# **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	5.6 cm
Package 1 Width	8 cm
Package 1 Length	39 cm
Package 1 Weight	770 g

### **Contractual warranty**

Warranty

18 months

## Sustainability

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

### Well-being performance

Reach Free Of Svhc

Toxic Heavy Metal Free

Mercury Free

Eq

Rohs Exemption Information Yes

## **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations