# Product data sheet

Specifications

## Wall mounting socket, Mureva PK, 125A, 3P+E, 400V, IP67

81194

## Main

| | |
|---|---|
| **Range** | Mureva |
| **Product Or Component Type** | Socket |
| **Device Short Name** | Mureva socket |
| **Plug, Socket Category** | Low voltage |
| **Poles Description** | 3P + E |
| **Network Type** | AC |
| **Outlet Standard** | Industrial |

## Complementary

| | |
|---|---|
| **Mounting Mode** | Wall-mounted |
| **Plug, Socket, Control Station Shape** | Angled |
| **[In] Rated Current** | 125 A |
| **[Ue] Rated Operational Voltage** | 380...415 V |
| **Network Frequency** | 50/60 Hz |
| **Ground Lug Clockwise Position** | 6 h |
| **Plug, Socket Material** | Housing: self-extinguishing engineering polymer |
| **Contacts Material** | Pins: stainless steel<br>Sleeves: nickel plated brass<br>Springs: stainless steel |
| **Connections - Terminals** | Captive screws, completely loosened |
| **Cable Cross Section** | 16…70 mm² |
| **Cable Entry** | Cable gland |
| **Thread Type** | Pg 48 |
| **Net Weight** | 1.932 kg |
| **Base Dimension** | 114 x 224 mm |
| **Height** | 340 mm |
| **Width** | 114 mm |
| **Depth** | 213 mm |
| **Colour** | Grey (RAL 7035) |
| **Voltage Colour** | Red |

## Environment

| Standards | EN 60309-1 |
| --- | --- |
| | EN 60309-2 |
| Ip Degree Of Protection | IP67 conforming to IEC 60529 |
| Ik Degree Of Protection | IK08 conforming to EN 62262 |
| Fire Resistance | 850 °C conforming to IEC 60695-2-11 |
| Relative Humidity | 50 % at 40 °C |
| | 70 % at 30 °C |
| | 90 % at 20 °C |
| Ambient Air Temperature For Operation | 35 °C ( 86400 s ) |

## Packing Units

| Unit Type Of Package 1 | PCE |
| --- | --- |
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 13.0 cm |
| Package 1 Width | 18.6 cm |
| Package 1 Length | 38.2 cm |
| Package 1 Weight | 1.938 kg |
| Unit Type Of Package 2 | S03 |
| Number Of Units In Package 2 | 2 |
| Package 2 Height | 30.0 cm |
| Package 2 Width | 30.0 cm |
| Package 2 Length | 40.0 cm |
| Package 2 Weight | 4.363 kg |

## Contractual warranty

| Warranty | 18 months |
| --- | --- |

# Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-$CO_2$ products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium ⟩

Guide to assess a product's sustainability ⟩

Transparency    RoHS/REACh

## Well-being performance

✓ Rohs Exemption Information         Yes

## Certifications & Standards

**Reach Regulation**                    REACh Declaration

**Eu Rohs Directive**                    Pro-active compliance (Product out of EU RoHS legal scope)

**China Rohs Regulation**              China RoHS declaration

Product out of China RoHS scope. Substance declaration for your information

**Environmental Disclosure**           Product Environmental Profile

**Circularity Profile**                  No need of specific recycling operations