Product data sheet

Specifications



industrial socket - 16 A - 2P - 400 V AC - IP 65 - panel

82077

() Discontinued on: Jun 30, 2022

Main

Range	PratiKa
Product Or Component Type	Interlocked socket
Device Short Name	PK Unika socket
Plug, Socket Category	Extra-low voltage
Poles Description	2P
Network Type	AC
Outlet Standard	Industrial

Complementary

J	
[In] Rated Current	16 A
[Ue] Rated Operational Voltage	400 V
Output Voltage	24 V
Network Frequency	50/60 Hz
Ground Lug Clockwise Position	Without
Secondary Keyway Clockwise Position	Without
Transformer Rated Power In Va	160 VA
Fuse Type	Cylindrical
Fuse Size	Without
Plug, Socket Material	Housing: self-extinguishing engineering polymer
Contacts Material	Sleeves: nickel plated brass
Connections - Terminals	Captive screws
Maximum Cable Cross Section	6 mm ²
Maximum Cable Outer Diameter	25 mm
Cable Entry	Cable gland
Thread Type	Pg 21
Base Dimension	103 x 225 mm
Height	225 mm
Width	103 mm
Depth	127 mm
Colour	Violet (RAL 7035)

Voltage Colour

Violet

Environment

Standards	IEC 309-1
	EN 50102
	IEC 309-2
	IEC 695-2-1
	IEC 742
	IEC 529
Ip Degree Of Protection	IP65 conforming to IEC 529
Ik Degree Of Protection	IK09 conforming to EN 50102
Fire Resistance	750 °C conforming to IEC 60695-2-1
Relative Humidity	50 % at 40 °C
	70 % at 30 °C
	90 % at 20 °C
Ambient Air Temperature For Operation	35 °C (86400 s)

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	10.3 cm
Package 1 Width	16.5 cm
Package 1 Length	26 cm
Package 1 Weight	2.359 kg

Sustainability

প্লি

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Lower Impact Materials Transparency RoHS/REACh

Fa

Resource performance

Minimum Percentage Of Recycled ⁴⁶ Plastic Content

Well-being performance

Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations