Specifications



# selector switch Ø 30 - black - 2 positions - maintained

9001KS12K1E43

() Discontinued on: Dec 19, 2019

#### (!) Discontinued

#### Main

| Range Of Product          | Harmony 9001KS   |
|---------------------------|------------------|
| Product Or Component Type | Selector switch  |
| Device Short Name         | 9001KS           |
| Type Of Operator          | maintained       |
| Operator Profile          | Black key switch |

## Complementary

| Bezel Material                | Chromium plated metal |
|-------------------------------|-----------------------|
| Mounting Diameter             | 30 mm                 |
| Net Weight                    | 0.245 kg              |
| Shape Of Signaling Unit Head  | Round                 |
| Operator Position Information | 2 positions           |
| Key Number                    | E43                   |
| Key Withdrawal Position       | Left                  |
| Contacts Type And Composition | Without contact block |
| Mechanical Durability         | 500000 cycles         |
| Device Presentation           | Basic element         |

## Environment

| Protective Treatment                     | тс  |
|--|---|
| Ambient Air Temperature For<br>Storage   | -4070 °C  |
| Ambient Air Temperature For<br>Operation | -2570 °C  |
| Overvoltage Category                     | Class II conforming to IEC 61140  |
| Ip Degree Of Protection                  | IP66 conforming to IEC 60529  |
| Nema Degree Of Protection                | NEMA 1<br>NEMA 12<br>NEMA 13<br>NEMA 2<br>NEMA 3<br>NEMA 3R<br>NEMA 4<br>NEMA 6 |

| Standards              | CSA C22.2 No 14                               |  |
|------------------------|---|--|
|                        | EN/IEC 60947-1                                |  |
|                        | EN/IEC 60947-5-1                              |  |
|                        | JIS C 852                                     |  |
|                        | EN/IEC 60947-5-4                              |  |
|                        | UL 508  |  |
|                        | JIS C 4520                                    |  |
| Product Certifications | NEMA  |  |
|                        | UL 508  |  |
| Vibration Resistance   | 7 gn (f= 2500 Hz) conforming to IEC 60068-2-6 |  |
| Charle Desistance      |   |  |

Shock Resistance

50 gn conforming to IEC 60068-2-27

## Sustainability

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Yes

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

#### Well-being performance



Eq

Rohs Exemption Information

## **Certifications & Standards**

| Reach Regulation          | REACh Declaration  |
|---------------------------|--|
| Eu Rohs Directive         | Pro-active compliance (Product out of EU RoHS legal scope)   |
| China Rohs Regulation     | China RoHS declaration   |
| Environmental Disclosure  | Product Environmental Profile  |
| Weee                      | The product must be disposed on European Union markets following specific waste<br>collection and never end up in rubbish bins   |
| Circularity Profile       | No need of specific recycling operations   |
| California Proposition 65 | WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |