



Main

| | |
|---------------------------|------------------|
| Range of product | 9007 |
| Series name | Miniature potted |
| Product or component type | Limit switch |
| Device short name | 9007MS/ML |
| Sensor design | Miniature |
| Body type | Fixed |
| Head type | Plunger head |
| Material | Metal |
| Body material | Cast zinc |
| Number of poles | 1 |

Complementary

| | |
|--------------------------------|---|
| Fixing mode | By the body |
| Movement of operating head | Linear |
| Type of operator | Spring return plunger stainless steel (booted) |
| Type of approach | Vertical approach 1 direction |
| Switch actuation | On end |
| Contacts type and composition | NC-NO |
| Switch function | SPDT |
| Contact form | Form C |
| Contacts material | Silver contacts |
| Contact operation | Snap action |
| Positive opening | Without |
| Electrical connection | Pre-wired cable bottom |
| Type of cable | SJTO cable (AWG 18), 18 ft, yellow |
| Terminals description ISO n°1 | (green-yellow)gnd (black)com (white)NO (red)NC |
| Wire insulation material | PVC |
| Maximum force for tripping | 80 ozf |
| [Ie] rated operational current | 6 A at 120 V AC, A300 conforming to NEMA rating designation |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

3 A at 240 V AC, A300 conforming to NEMA rating designation
5 A at 28 V DC

| | |
|--|---|
| [Ithe] conventional enclosed thermal current | 10 A |
| [U] rated insulation voltage | 300 V degree of pollution 3 conforming to CSA C22.2 No 14 300 V degree of pollution 3 conforming to UL 508 |
| Electrical durability | 100000 cycles |
| Mechanical durability | 10000000 cycles |
| Marking | CE CSA UL |
| Sale per indivisible quantity | 1 |
| Height | 1.75 in |
| Width | 1.56 in |
| Depth | 0.62 in |
| Product weight | 1.2 lb(US) |

Environment

| | |
|---------------------------------------|---|
| Shock resistance | 35 gn (duration = 9 ms) conforming to IEC 60068-2-27 |
| Vibration resistance | 10 gn (f = 75...1200 Hz) conforming to IEC 60068-2-6 |
| NEMA degree of protection | NEMA 2 conforming to Nema type 250 NEMA 4 conforming to Nema type 250 NEMA 6 conforming to Nema type 250 NEMA 6P conforming to Nema type 250 NEMA 1 conforming to Nema type 250 |
| IP degree of protection | IP67 conforming to IEC 60529 |
| Ambient air temperature for operation | -40...220 °F |
| Ambient air temperature for storage | -40...220 °F |
| Protective treatment | Epoxy powder coat |
| Product certifications | CE CSA UL |
| Standards | LR 25490 Class 32 11 03 E78403 |

Offer Sustainability

| | |
|----------------------------------|--|
| RoHS (date code: YYWW) | Will not be compliant Will not be compliant |
| REACH | Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold |
| Product environmental profile | Available |
| Product end of life instructions | Need no specific recycling operations |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|