



### Main

Range of product	Acti 9
Product name	Acti 9 iPC
Product or component type	Modular socket-outlet
Device short name	IPC
Poles description	2P + E
Outlet standard	Italian

### Complementary

[In] rated current	16 A
[Ue] rated operational voltage	250 V AC 50/60 Hz
Mounting mode	Fixed
Mounting support	Symmetrical DIN rail
9 mm pitches	5
Height	87 mm
Width	44 mm
Depth	60 mm
Product weight	98 g
Colour	White
Connections - terminals	Tunnel type terminal 1 cable(s) flexible 6 mm <sup>2</sup> Tunnel type terminal 1 cable(s) rigid 10 mm <sup>2</sup>
Wire stripping length	13 mm
Tightening torque	1.2 N.m

### Environment

Standards	IEC 23-16
IP degree of protection	IP40 (in modular enclosure) conforming to IEC 60529 IP20 conforming to IEC 60529
IK degree of protection	IK03
Tropicalisation	2 conforming to IEC 60068-1
Relative humidity	95 % ( 55 °C )
Ambient air temperature for operation	-25...70 °C

---

Ambient air temperature for storage	-40...80 °C
-------------------------------------	-------------

---

### Offer Sustainability

---

RoHS (date code: YYWW)	Compliant - since 1312 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>

---

### Contractual warranty

---

Warranty period	18 months
-----------------	-----------

---