



Main

Range of product	Acti 9
Product or component type	Remote indication auxiliary
Device short name	ISR
Signal contacts composition	1 C/O
[In] rated current	3 A at 380...415 V AC - 50/60 Hz 6 A at 220...240 V AC - 50/60 Hz 1 A at 130 V DC 1.5 A at 60 V DC 2 A at 48 V DC 6 A at 24 V DC
9 mm pitches	1

Complementary

Range compatibility	Acti 9 iQuick PF Acti 9 iQuick PRD Acti 9 iPF Acti 9 iPRC
Mounting mode	Fixed
Mounting support	DIN rail
Height	84 mm
Width	9 mm
Depth	69 mm
Colour	White
Connections - terminals	Clamp terminal in bottom 3 cable(s) 0.16 mm ² rigid Clamp terminal in bottom 6 cable(s) 0.16 mm ² flexible Clamp terminal in bottom 1 cable(s) 0.16 mm ² flexible with ferrule
Wire stripping length	9 mm
Tightening torque	1 N.m 1.2 N.m

Environment

Standards	EN/IEC 60947-5-1
IP degree of protection	IP20 conforming to EN/IEC 60947-5-1
Tropicalisation	2 conforming to EN/IEC 60947-5-1

Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-25...50 °C
Ambient air temperature for storage	-40...85 °C

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 1001 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
------------------------	---

Contractual warranty

Warranty period	18 months
-----------------	-----------
