

2 adapter boards - basic - current on all circuits

BCPMSCC1S

- ! To be discontinued on: Dec 31, 2024
- ! To be end-of-service on: Dec 31, 2032

(!) To be discontinued

Main

| mann | | |
|---------------------------|---------------------------------|--|
| Range | PowerLogic | |
| Product Name | PowerLogic BCPMSC | |
| Product Or Component Type | Multi-circuit energy meter | |
| Device Short Name | BCPMSCC | |
| Model Type | Basic | |
| Power Monitoring | Basic instrumentation | |
| Energy Management | Sub billing and cost allocation | |
| Device Application | Sub billing | |
| Type Of Measurement | Current | |
| [Us] Rated Supply Voltage | 90277 V AC 50/60 Hz +/- 1 % | |
| Network Frequency | 50 Hz 60 Hz | |

Complementary

| Current Transformer Input | Current 0.333 V42 x Current 1 V | |
|-----------------------------|---|--|
| Update Time | 1.8 s | |
| Measurement Voltage | 90277 V phase to neutral 150480 V phase to phase | |
| Measurement Accuracy | Current 2 % 0.252 A Current 1 % 2100 A | |
| Sampling Rate | 256 samples/cycle | |
| Provided Equipment | 2 x adapter board 0 x current transformer | |
| Communication Port Protocol | Modbus RTU | |
| Communication Port Support | RS485 | |
| Communication Of Data | High-high current alarm High current alarm Low current alarm Low-low current alarm | |

Environment

| Mounting Mode | Clip-on |
|------------------|---------|
| Mounting Support | Board |

| Relative Humidity | 95 % |
|---------------------------------------|-------------------------|
| Ambient Air Temperature For Operation | 060 °C |
| Ambient Air Temperature For Storage | -4070 °C |
| Operating Altitude | 3000 m |
| Standards | IEC 61010-1 EN 61010 |
| Product Certifications | UL 508 |
| Width | 288 mm |
| Height | 146 mm |
| Net Weight | 1.5 kg |

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|----------|
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 10.4 cm |
| Package 1 Width | 31.1 cm |
| Package 1 Length | 38.7 cm |
| Package 1 Weight | 1.182 kg |

Contractual warranty

Warranty 18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Yes

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance

Rohs Exemption Information

| Mercury Free |
|--------------|
| |

| Reach Regulation | REACh Declaration |
|-----------------------|---------------------------|
| Eu Rohs Directive | Compliant with Exemptions |
| China Rohs Regulation | China RoHS declaration |