

# Product data sheet

Specifications



## Touch panel, Wiser, wall mounted kit, white

CCT501500

⚠ Discontinued on: Sep 7, 2022

⚠ Discontinued

### Main

Product Brand	Schneider Electric
Range	Wiser
Product Name	Wiser Home Touch
Product Or Component Type	Touch panel
Concentrator Compatibility	Wiser hub generation 1 Wiser hub generation 2
Device Presentation	Complete product
Mobile App Name	Wiser Home

### Complementary

Colour Tint	White (RAL 9003)
[Ue] Rated Operational Voltage	24 V DC
[In] Rated Current	0.25 A
Overvoltage Category	Class II
Display Type	Colour touchscreen
Display Resolution	640 x 480 pixels VGA
Display Size	89 mm
Sensor Type	Light level sensor auto dimming Occupancy sensor wake-up Temperature Humidity sensor
Temperature Setting Range	7.5...33 °C heating 0.5 °C per step 9...35 °C cooling
Information Displayed	Temperature: 5...35 °C
Measurement Accuracy	Temperature: 0.5 °C, Humidity: +/- 3 %,
Software Name	Wiser App: upgrade device firmware
Communication Network Type	Wireless Zigbee (2.4 GHz), 2.5 mW at < 50 m
Mounting Mode	Wall-mounted
Mounting Position	Horizontal
Type Of Installation	Indoor
Service Life	10 year(s)
Meantime Between Failure [Mtbef]	8 year(s) at 25 °C

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Device Composition	fixing frame 95 mm x 95 mm x 5 mm trim plate 120 mm x 160 mm x 6 mm terminal plate 78 mm x 77 mm x 14 mm screen 100 mm x 100 mm x 24 mm power supply 42 mm x 42 mm x 25 mm
Depth	34.2 mm with all the plates:

## Environment

Ambient Air Temperature For Operation	0...40 °C
Ambient Air Temperature For Storage	-30...50 °C
Relative Humidity	0...75 % non-condensing
Pollution Degree	2
Electromagnetic Compatibility	Radiated emission conforming to EN 300-328 Electromagnetic field immunity test conforming to EN 301-489-1 Electrostatic discharge conforming to EN 301-489-1 Fast transients immunity test conforming to EN 301-489-1 Immunity to voltage dips conforming to EN 301-489-1 Surges conforming to EN 301-489-1
Standards	IEC 60730-1 EN 60730 IEEE 802.11b/g/n

## Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	13 cm
Package 1 Width	13.7 cm
Package 1 Length	17.5 cm
Package 1 Weight	565 g

# Sustainability

**Green Premium™ label** is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



## Transparency

Eu Rohs Directive	Under investigation
China Rohs Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	<a href="#">End of Life Information</a>