Product data sheet

Specifications





Stago - c bracket - 300 mm - electro-galvanized

CSU08173309

() Discontinued on: Jan 3, 2022

Important message: This product belongs to Cable Support which is no longer commercialized by Schneider Electric. As per the first of January 2022 the commercialization is managed by Wibe-Group, Please follow the link www.wibe-group.com for further details.

Main

Range Of Product	Stago
Product Or Component Type	Ceiling bracket
Mounting Location	Heated facility with low exposure to corrosion hotels and offices

Complementary

Completionally		
Shape	C-shape	
Product Destination	KB184 cable tray 300 mm width KB284 cable tray 300 mm width fibre optic cable duct	
Fixing Mode	By screw	
Material With Surface Treatment	Steel electro-galvanized	
Corrosion Class	C1	
Height	240 mm	
Width	340 mm	
Depth	175 mm	
Net Weight	1.53 kg / set of 1	

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	18 cm
Package 1 Width	24 cm
Package 1 Length	34 cm
Package 1 Weight	2 kg

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc

Toxic Heavy Metal Free

Mercury Free

Eq

Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations