Specifications



(!) Discontinued

Stago - internal riser formed -60x120 mm - steel - pre-galvanized - RAL9010

CSU08642079

(!) Discontinued on: Jan 3, 2022

Important message: This product belongs to Cable Support which is no longer commercialized by Schneider Electric. As per the first of January 2022 the commercialization is managed by Wibe-Group, Please follow the link www.wibe-group.com for further details.

Main

Range Of Product	Stago
Range	Stago
Product Or Component Type	Riser
Device Application	Cable management

Complementary

Operating Angle90 °Direction Change TypeVerticalInner Radius180 mmAdjustmentFixedShapeBendedProduct DestinationCable tray KG281 H= 60 mm W= 120 mmFixing ModeBy screwMaterial With Surface TreatmentSteel pre-galvanized, RAL 9010Corrosion ClassC2Thickness1 mmNet Weight1.018 kg	· · · · · · · · · · · · · · · · · ·	
Inner Radius180 mmAdjustmentFixedShapeBendedProduct DestinationCable tray KG281 H= 60 mm W= 120 mmFixing ModeBy screwMaterial With Surface TreatmentSteel pre-galvanized, RAL 9010Corrosion ClassC2Thickness1 mm	Operating Angle	90 °
Adjustment Fixed Shape Bended Product Destination Cable tray KG281 H= 60 mm W= 120 mm Fixing Mode By screw Material With Surface Treatment Steel pre-galvanized, RAL 9010 Corrosion Class C2 Thickness 1 mm	Direction Change Type	Vertical
Shape Bended Product Destination Cable tray KG281 H= 60 mm W= 120 mm Fixing Mode By screw Material With Surface Treatment Steel pre-galvanized, RAL 9010 Corrosion Class C2 Thickness 1 mm	Inner Radius	180 mm
Product Destination Cable tray KG281 H= 60 mm W= 120 mm Fixing Mode By screw Material With Surface Treatment Steel pre-galvanized, RAL 9010 Corrosion Class C2 Thickness 1 mm	Adjustment	Fixed
Fixing Mode By screw Material With Surface Treatment Steel pre-galvanized, RAL 9010 Corrosion Class C2 Thickness 1 mm	Shape	Bended
Material With Surface Treatment Steel pre-galvanized, RAL 9010 Corrosion Class C2 Thickness 1 mm	Product Destination	Cable tray KG281 H= 60 mm W= 120 mm
Corrosion Class C2 Thickness 1 mm	Fixing Mode	By screw
Thickness 1 mm	Material With Surface Treatment	Steel pre-galvanized, RAL 9010
	Corrosion Class	C2
Net Weight 1.018 kg	Thickness	1 mm
	Net Weight	1.018 kg

Environment

Mounting Location

Partly outdoor environment with low exposure to corrosion ware-houses and parking garages

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Eq

Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc
Toxic Heavy Metal Free

Mercury Free

Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations