

Product data sheet

Specifications



Stago - t-piece formed 110x200mm stainless steel AISI 304

CSU71632030

⚠ Discontinued on: Jan 3, 2022

⚠ Discontinued

Main

Product Or Component Type	T-piece
---------------------------	---------

Complementary

Operating Angle	90 °
Direction Change Type	Vertical
Adjustment	Fixed
Product Destination	Cable tray ES114 H= 110 mm W= 200 mm
Fixing Mode	By screw
Material	Stainless steel AISI 304
Inner Radius	100 mm

Environment

Atmospheric-Corrosivity Category	C5-I
Environmental Characteristic	Area with almost permanent high levels of humidity and airborne pollution tunnels and dockyards
Net Weight	4.234 kg

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	11 cm
Package 1 Width	60 cm
Package 1 Length	40 cm
Package 1 Weight	2.789 kg

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

✓ Reach Free Of Svhc

✓ Toxic Heavy Metal Free

✓ Mercury Free

✓ Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation	REACH Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations