Product data sheet

Specifications



Category 5e, UTP Keystone, Modular Jack, Blue

DCEKYSTUBL

() Discontinued on: Aug 4, 2021

(!) Discontinued

Main

Range Of Product	Digilink
Product Or Component Type	Modular jack
Cable Shielding Type	UTP
Communication Network Category	5e
Colour Tint	Blue

Complementary

· · · · · · · · · · · · · · · · · ·	
Connector Type	RJ45
Type Of Footprint	Keystone
Insulation Resistance	>= 500 mOhm at 500 V DC
Minimum Number Of Matings	750 cycles
Contacts Material	Phosphor bronze with 50 micro-inches gold over 100 micro-inches nickel
Pulling Force	140 N
Delay Skew	2.5 ns at 1100 MHz
[In] Rated Current	1.5 A
Contact Resistance	20 mOhm
[Ue] Rated Operational Voltage	< 72 V DC

Environment

Flame Retardance	V-0 conforming to UL 94
Product Certifications	UL/ETL verified UL listed
Standards	ANSI/TIA-568-C.2 ISO/IEC 11801 class D

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	1 cm
Package 1 Width	9 cm
Package 1 Length	15 cm
Package 1 Weight	10 g

Contractual warranty

Warranty

18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency

Well-being performance

Toxic Heavy Metal Free Mercury Free Rohs Exemption Information Yes Compliant **Eu Rohs Directive** EU RoHS Declaration **China Rohs Regulation** China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope) **Environmental Disclosure** Product Environmental Profile The product must be disposed on European Union markets following specific waste Weee collection and never end up in rubbish bins No need of specific recycling operations **Circularity Profile**