

Switched socket, AvatarOn, screw terminal, IP20, wine gold

E8315_WG_C5

Main

| Product Or Component Type | Switched socket |
|----------------------------|------------------|
| Device Application | Power supply |
| Device Presentation | Complete product |
| Outlet Poles Configuration | 3P with shutter |
| Type Of Packing | Flow-pack |

Complementary

| Rated Current | 13 A socket-outlet |
|--------------------------------|--|
| [Ue] Rated Operational Voltage | 250 V AC 50/60 Hz |
| Socket Number | 1 |
| Outlet Standard Description | With earthing contact |
| Outlet Standard | British BS 1363A |
| Number Of Gangs | 1 gang |
| Service Life In Cycles | 20000 cycles |
| Electrical Durability | 5000 cycles |
| Connections - Terminals | Screw terminal |
| Material | Polycarbonate: grid plate Polycarbonate: surround |
| Surface Finish | Glossy |
| Surface Treatment | Painted cover plate |
| Device Mounting | Surface |
| Fixing Mode | Screw |
| Height | 86 mm |
| Width | 86 mm |
| Depth | 31.7 mm |

Environment

| Ip Degree Of Protection | IP20 |
|---------------------------------------|---------|
| Ambient Air Temperature For Operation | -545 °C |
| Ambient Air Temperature For Storage | -560 °C |
| Relative Humidity | 095 % |

| Product Certifications | SIRIM | |
|------------------------|---------|--|
| | BS 1363 | |
| | SS 145 | |
| Standards | MS 589 | |

Packing Units

| I acking Office | |
|------------------------------|----------|
| Unit Type Of Package 1 | PCE |
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 3.2 cm |
| Package 1 Width | 8.6 cm |
| Package 1 Length | 8.6 cm |
| Package 1 Weight | 83.0 g |
| Unit Type Of Package 2 | BB1 |
| Number Of Units In Package 2 | 12 |
| Package 2 Height | 9.5 cm |
| Package 2 Width | 19.0 cm |
| Package 2 Length | 19.5 cm |
| Package 2 Weight | 1.036 kg |
| Unit Type Of Package 3 | CAR |
| Number Of Units In Package 3 | 72 |
| Package 3 Height | 21.0 cm |
| Package 3 Width | 30.0 cm |
| Package 3 Length | 39.5 cm |
| Package 3 Weight | 6717.0 g |

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

| Ø | Reach Free Of Svhc | |
|----------|----------------------------|-----|
| ⊘ | Toxic Heavy Metal Free | |
| ⊘ | Mercury Free | |
| ⊘ | Rohs Exemption Information | Yes |

Certifications & Standards

| Reach Regulation | REACh Declaration |
|--------------------------|---|
| Eu Rohs Directive | Compliant EU RoHS Declaration |
| China Rohs Regulation | China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope) |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |