

2 Switch, AvatarOn, 1-pole 1-way, LED, brass terminal, IP20, wood

E8332L1LED_WD_C5

Main

Product Or Component Type	Switch
Device Application	Control
Load Type	Fluorescent lamp
	Incandescent lamp
	Resistive
	Inductive
Colour Tint	Wood

Complementary

Device Presentation Complete product Rated Current 16 AX at 250 V AC 50/60 Hz Switch Function 1-pole 1-way Number Of Gangs 2 gangs Number Of Rocker 2 Clamping Connection Capacity 3 x 2.5 mm² for solid cable(s) 3 x 2.5 mm² for stranded cable(s) 4 x 1.5 mm² for solid cable(s) Connections - Terminals Brass terminal Local Signalling Off: LED indicator, LED (amber) Material Polycarbonate: grid plate Polycarbonate: dolly Polycarbonate: frame Polycarbonate + GF 20 %: actuator Device Mounting Surface Flush Width 86 mm			
Switch Function 1-pole 1-way Number Of Gangs 2 gangs Number Of Rocker 2 Clamping Connection Capacity 3 x 2.5 mm² for solid cable(s) 3 x 2.5 mm² for stranded cable(s) 4 x 1.5 mm² for stranded cable(s) 4 x 1.5 mm² for stranded cable(s) Connections - Terminals Brass terminal Local Signalling Off: LED indicator, LED (amber) Material Polycarbonate: grid plate Polycarbonate: base Polycarbonate: dolly Polycarbonate: frame Polycarbonate + GF 20 %: actuator Device Mounting Surface Flush Width 86 mm	Device Presentation	Complete product	
Number Of Gangs 2 gangs Number Of Rocker 2 Clamping Connection Capacity 3 x 2.5 mm² for solid cable(s) 3 x 2.5 mm² for stranded cable(s) 4 x 1.5 mm² for solid cable(s) 4 x 1.5 mm² for stranded cable(s) Connections - Terminals Brass terminal Local Signalling Off: LED indicator, LED (amber) Material Polycarbonate: grid plate Polycarbonate: base Polycarbonate: dolly Polycarbonate: frame Polycarbonate + GF 20 %: actuator Device Mounting Surface Flush Width 86 mm	Rated Current	16 AX at 250 V AC 50/60 Hz	
Number Of Rocker 2 Clamping Connection Capacity 3 x 2.5 mm² for solid cable(s) 3 x 2.5 mm² for stranded cable(s) 4 x 1.5 mm² for stranded cable(s) 4 x 1.5 mm² for stranded cable(s) Connections - Terminals Brass terminal Local Signalling Off: LED indicator, LED (amber) Material Polycarbonate: grid plate Polycarbonate: base Polycarbonate: dolly Polycarbonate: frame Polycarbonate + GF 20 %: actuator Device Mounting Surface Flush Width 86 mm	Switch Function	1-pole 1-way	
Clamping Connection Capacity 3 x 2.5 mm² for solid cable(s) 3 x 2.5 mm² for stranded cable(s) 4 x 1.5 mm² for solid cable(s) 4 x 1.5 mm² for stranded cable(s) Connections - Terminals Brass terminal Local Signalling Off: LED indicator, LED (amber) Material Polycarbonate: grid plate Polycarbonate: base Polycarbonate: dolly Polycarbonate: frame Polycarbonate + GF 20 %: actuator Device Mounting Surface Flush Width 86 mm	Number Of Gangs	2 gangs	
3 x 2.5 mm² for stranded cable(s) 4 x 1.5 mm² for solid cable(s) 4 x 1.5 mm² for stranded cable(s) Connections - Terminals Brass terminal Decal Signalling Off: LED indicator, LED (amber) Material Polycarbonate: grid plate Polycarbonate: base Polycarbonate: dolly Polycarbonate: frame Polycarbonate + GF 20 %: actuator Device Mounting Surface Flush Width 86 mm	Number Of Rocker	2	
Local Signalling Off: LED indicator, LED (amber) Material Polycarbonate: grid plate Polycarbonate: base Polycarbonate: dolly Polycarbonate: frame Polycarbonate + GF 20 %: actuator Device Mounting Surface Flush Width 86 mm	Clamping Connection Capacity	3 x 2.5 mm² for stranded cable(s) 4 x 1.5 mm² for solid cable(s)	
Material Polycarbonate: grid plate Polycarbonate: base Polycarbonate: dolly Polycarbonate: frame Polycarbonate + GF 20 %: actuator Device Mounting Surface Flush Width 86 mm	Connections - Terminals	Brass terminal	
Polycarbonate: base Polycarbonate: base Polycarbonate: dolly Polycarbonate: frame Polycarbonate + GF 20 %: actuator Device Mounting Surface Flush Width 86 mm	Local Signalling	Off: LED indicator, LED (amber)	
Flush Width 86 mm	Material	Polycarbonate: base Polycarbonate: dolly Polycarbonate: frame	
	Device Mounting		
- Unight 00	Width	86 mm	
riegit oo mm	Height	86 mm	
Depth 34.2 mm	Depth	34.2 mm	

Environment

Ip Degree Of Protection	IP20
Maximum Ambient Air Temperature For Operation	45 °C
Operating Altitude	2000 m
Relative Humidity	095 %
Environmental Characteristic	UV resistant

Standards MS IEC 60669-1

IEC 60669-1 BS EN 60669-1 SS 227-1

Packing Units

_	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.4 cm
Package 1 Width	8.6 cm
Package 1 Length	8.6 cm
Package 1 Weight	94.0 g
Unit Type Of Package 2	CAR
Number Of Units In Package 2	10
Package 2 Height	9.5 cm
Package 2 Width	19.0 cm
Package 2 Length	19.5 cm
Package 2 Weight	1033.0 g

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations