

AvatarOn, TV R socket, master, 75 Ohm, Wood

E8332TVFMM_WD_C5

Main

Product Or Component Type	TV R socket
Device Application	Communication
Tv Socket Type	TV/FM
Number Of Gangs	2 gangs
Colour Tint	Wood

Complementary

Device Presentation	Complete product
Device Mounting	Surface Flush
Method Of Access	Master
Average Impedance	75 Ohm
Material	Polycarbonate: surround Polycarbonate: grid plate
Bandwidth	5860 MHz
Colour Tint	Wood
Ip Degree Of Protection	IP20
Width	86 mm
Height	86 mm
Depth	23.6 mm

Environment

Ambient Air Temperature For Operation	-545 °C
Relative Humidity	095 %
Standards	BS 5733 IEC 60670

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	2.4 cm
Package 1 Width	8.6 cm
Package 1 Length	8.6 cm

Package 1 Weight	81.0 g
Unit Type Of Package 2	BB1
Number Of Units In Package 2	10
Package 2 Height	9.5 cm
Package 2 Width	19.0 cm
Package 2 Length	19.5 cm
Package 2 Weight	982.0 g
Unit Type Of Package 3	CAR
Number Of Units In Package 3	60
Package 3 Height	21.0 cm
Package 3 Width	30.0 cm
Package 3 Length	39.5 cm
Package 3 Weight	5894.0 g

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations