

4 Switch, AvatarOn, 1-pole 2-way, brass terminal, IP20, wood

E8334L2_WD_G11

Discontinued on: Jun 30, 2023

! Discontinued

Main

Product Or Component Type	Switch
Device Application	Control
Load Type	Inductive
	Incandescent lamp
	Fluorescent lamp
	Resistive
Colour Tint	Wood

Complementary

Device Presentation Complete product Rated Current 16 AX at 250 V AC 50/60 Hz Switch Function 1-pole 2-way Number Of Gangs 4 gangs Number Of Rocker 4 Clamping Connection Capacity 3 x 2.5 mm² for solid cable(s) 3 x 2.5 mm² for solid cable(s) 4 x 1.5 mm² for solid cable(s) 4 x 1.5 mm² for stranded cable(s) Connections - Terminals Brass terminal Material Polycarbonate: grid plate Polycarbonate: frame Polycarbonate: frame Polycarbonate: frame Polycarbonate + GF 20 %: actuator Device Mounting Surface Flush Width 86 mm Height 86 mm Depth 34.2 mm	•	
Switch Function 1-pole 2-way Number Of Gangs 4 gangs Number Of Rocker 4 Clamping Connection Capacity 3 x 2.5 mm² for solid cable(s) 3 x 2.5 mm² for stranded cable(s) 4 x 1.5 mm² for solid cable(s) 4 x 1.5 mm² for stranded cable(s) Connections - Terminals Brass terminal Material Polycarbonate: grid plate Polycarbonate: base Polycarbonate: dolly Polycarbonate: frame Polycarbonate + GF 20 %: actuator Device Mounting Surface Flush Width 86 mm Height 86 mm	Device Presentation	Complete product
Number Of Gangs 4 gangs Number Of Rocker 4 Clamping Connection Capacity 3 x 2.5 mm² for solid cable(s) 3 x 2.5 mm² for stranded cable(s) 4 x 1.5 mm² for solid cable(s) 4 x 1.5 mm² for stranded cable(s) Connections - Terminals Brass terminal Material Polycarbonate: grid plate Polycarbonate: base Polycarbonate: dolly Polycarbonate: frame Polycarbonate: frame Polycarbonate + GF 20 %: actuator Device Mounting Surface Flush Width 86 mm Height 86 mm	Rated Current	16 AX at 250 V AC 50/60 Hz
Number Of Rocker Clamping Connection Capacity 3 x 2.5 mm² for solid cable(s) 3 x 2.5 mm² for stranded cable(s) 4 x 1.5 mm² for stranded cable(s) 4 x 1.5 mm² for stranded cable(s) Connections - Terminals Brass terminal Polycarbonate: grid plate Polycarbonate: base Polycarbonate: dolly Polycarbonate: frame Polycarbonate: frame Polycarbonate + GF 20 %: actuator Device Mounting Surface Flush Width 86 mm Height 86 mm	Switch Function	1-pole 2-way
Clamping Connection Capacity 3 x 2.5 mm² for solid cable(s) 3 x 2.5 mm² for stranded cable(s) 4 x 1.5 mm² for solid cable(s) 4 x 1.5 mm² for stranded cable(s) Connections - Terminals Brass terminal Polycarbonate: grid plate Polycarbonate: base Polycarbonate: dolly Polycarbonate: frame Polycarbonate + GF 20 %: actuator Device Mounting Surface Flush Width 86 mm Height 86 mm	Number Of Gangs	4 gangs
3 x 2.5 mm² for stranded cable(s) 4 x 1.5 mm² for solid cable(s) 4 x 1.5 mm² for stranded cable(s) Connections - Terminals Brass terminal Polycarbonate: grid plate Polycarbonate: base Polycarbonate: dolly Polycarbonate: frame Polycarbonate + GF 20 %: actuator Device Mounting Surface Flush Width 86 mm Height 86 mm	Number Of Rocker	4
Material Polycarbonate: grid plate Polycarbonate: base Polycarbonate: dolly Polycarbonate: frame Polycarbonate + GF 20 %: actuator Device Mounting Surface Flush Width 86 mm Height 86 mm	Clamping Connection Capacity	3 x 2.5 mm² for stranded cable(s) 4 x 1.5 mm² for solid cable(s)
Polycarbonate: base Polycarbonate: dolly Polycarbonate: frame Polycarbonate + GF 20 %: actuator Device Mounting Surface Flush Width 86 mm Height 86 mm	Connections - Terminals	Brass terminal
Flush Width 86 mm Height 86 mm	Material	Polycarbonate: base Polycarbonate: dolly Polycarbonate: frame
Height 86 mm	Device Mounting	
	Width	86 mm
Depth 34.2 mm	Height	86 mm
	Depth	34.2 mm

Environment

Ip Degree Of Protection	IP20
Maximum Ambient Air Temperature For Operation	45 °C
Operating Altitude	2000 m
Relative Humidity	095 %
Environmental Characteristic	UV resistant

Standards BS EN 60669-1

MS IEC 60669-1 IEC 60669-1 SS 227-1

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.4 cm
Package 1 Width	8.6 cm
Package 1 Length	8.6 cm
Package 1 Weight	136.0 g
Unit Type Of Package 2	CAR
Number Of Units In Package 2	8
Package 2 Height	9.5 cm
Package 2 Width	19.0 cm
Package 2 Length	19.5 cm
Package 2 Weight	1199.0 g

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

✓ Reach Free Of Svhc
 ✓ Toxic Heavy Metal Free
 ✓ Mercury Free
 ✓ Rohs Exemption Information

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations