

# Product data sheet

Specifications



## Asfora - double USB charger 2.1 A - aluminium

EPH2700261

### Main

Range	Asfora
Product Or Component Type	USB charger
Device Presentation	Mechanism with fixing frame
Device Mounting	Flush

### Complementary

Device Application	Charger
Fixing Mode	By claws By screws
Number Output Current	2.1 A
Integrated Connection Type	2 USB 2.0 port 5 V DC, maximum load current: 2.1 A
[Ue] Rated Operational Voltage	100...240 V AC +/- 10 % at 50/60 Hz
Power Consumption In W	0.1 W
Nominal Output Power	10.5 W
Input Power	12 W
Surface Treatment	Untreated
Material	ABS (acrylonitrile butadiene-styrene): centre plate PC (polycarbonate) GF10 FR: casing PC (polycarbonate) GF10 FR: internal cover
Type Of Packing	Flow-pack
Clamping Connection Capacity	2 x 0.75...2 x 2.5 mm² for rigid cable(s) 2 x 0.75...2 x 2.5 mm² for flexible cable(s) 2 x 0.75...2 x 2.5 mm² for stranded cable(s)
Service Life In Hours	30000 h 10.5 W
Protection Type	Short-circuit protection
Number Of Terminals	2 screw terminals
Wire Stripping Length	8 mm
Product Compatibility	Mobile/tablet Mac iOS Mobile/tablet Android Mobile/tablet Windows
Ik Degree Of Protection	IK04
Ip Degree Of Protection	IP20
Height	83 mm
Width	83 mm
Depth	42 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Embedding Depth	30.8 mm
-----------------	---------

## Environment

Standards	EN 62684 ETSI EN 301 489-4 EN 60950-1
Directives	2006/95/EC - low voltage directive 2004/108/EC - electromagnetic compatibility
Ambient Air Temperature For Operation	0...40 °C
Ambient Air Temperature For Storage	-5...50 °C
Product Certifications	EAC
Electrical Insulation Class	Class II

## Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	6.000 cm
Package 1 Width	8.500 cm
Package 1 Length	8.500 cm
Package 1 Weight	115.000 g
Unit Type Of Package 2	S02
Number Of Units In Package 2	24
Package 2 Height	15.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	2.993 kg
Unit Type Of Package 3	P12
Number Of Units In Package 3	384
Package 3 Height	45.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	59.888 kg

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency   RoHS/REACH

## Well-being performance

✓ Toxic Heavy Metal Free

✓ Mercury Free

✓ Rohs Exemption Information   [Yes](#)

## Certifications & Standards

Reach Regulation	<a href="#">REACH Declaration</a>
Eu Rohs Directive	Compliant <a href="#">EU RoHS Declaration</a>
China Rohs Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations