

Product data sheet

Specifications



EVlink Wallbox Plus - T2S socket outlet with shutters - 3 phase - 16A/11kW

EVH3S11P04K

⚠ Discontinued - Service only

⚠ Discontinued on: Dec 31, 2023

⚠ To be end-of-service on: Dec 31, 2028

Main

Range	EVlink
Product Name	EVlink Wallbox Plus
Product Or Component Type	Charging station
Device Short Name	EVH3
Poles Description	3P + N
Mounting Mode	Wall-mounted
Max Power	11 kW 16 A
Number Of Charge Point	1
Connection To The Vehicle	Socket-outlet T2 with shutter right side
Access Control System	Key

Complementary

Rated Supply Voltage	380...415 V AC 50/60 Hz
Earthing System	IT with the addition of an isolating transformer when required by certain vehicles TT TN-S
Number Of Inputs	1
Input Type	Contact for power limitation Contact for delayed charging Digital for dynamic energy management to connect to French electronic electricity meters in single-phase
Control Type	1 white button, function: stop/restart 1 green button, function: cable unlocking
Local Signalling	1 multi-colour indicator light, function: status indication
Height	480 mm
Width	331.5 mm
Depth	170 mm
Net Weight	5.7 kg
Colour	White (RAL 9003) Grey (RAL 7016)
Standards	IEC 61851-1 IEC 61851-22 IEC 62196-1 IEC 62196-2

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Product Certifications	CE CB
------------------------	----------

Environment

Ip Degree Of Protection	IP54 conforming to IEC 60529
Ik Degree Of Protection	IK10 conforming to IEC 62262
Ambient Air Temperature For Operation	-30...50 °C
Ambient Air Temperature For Storage	-40...80 °C
Relative Humidity	5...95 %

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	27.200 cm
Package 1 Width	40.000 cm
Package 1 Length	53.700 cm
Package 1 Weight	8.090 kg
Unit Type Of Package 2	P06
Number Of Units In Package 2	4
Package 2 Height	75.000 cm
Package 2 Width	60.000 cm
Package 2 Length	80.000 cm
Package 2 Weight	44.376 kg

Sustainability

Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



Transparency RoHS/REACH

Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation	REACH Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information