



### Main

|                           |  |
|---------------------------|--|
| Range                     | EVlink   |
| Product name              | EVlink parking   |
| Product or component type | Charging station   |
| Device short name         | EVW1   |
| Poles description         | 3P + N for power circuit<br>1P + N for control circuit               |
| Mounting mode             | Wall-mounted   |
| Offer type                | Standard   |
| Rated supply voltage      | 400 V AC 50/60 Hz power circuit<br>230 V AC 50/60 Hz control circuit |
| Earthing system           | TN<br>TT   |
| Socket-outlet number      | 1  |
| Socket-outlet type        | Right side : T2  |
| Supply current            | 32 A   |
| Max power                 | 22 kW  |

### Complementary

|                        |   |
|------------------------|---|
| Control type           | 1 green illuminated push-button function : unlock flap<br>1 red push-button function : stop   |
| Local signalling       | 1 green LED flashing function: on charge<br>1 green LED function: available<br>1 orange LED function: reserved<br>1 red LED function: not operational |
| Standards              | IEC 61851-1<br>IEC 61851-22   |
| Product certifications | CE<br>CB  |
| Height                 | 620 mm  |
| Width                  | 413 mm  |

|                |        |
|----------------|--------|
| Depth          | 256 mm |
| Product weight | 33 kg  |

## Environment

|                                       |   |
|---------------------------------------|---|
| IP degree of protection               | IP54 off load conforming to IEC 61851-1<br>IP54 on load conforming to IEC 61851-1                 |
| IK degree of protection               | IK10 charging station conforming to IEC 61851-22<br>IK08 socket-outlet conforming to IEC 61851-22 |
| Ambient air temperature for operation | -30...50 °C conforming to IEC 61851-22  |
| Ambient air temperature for storage   | -40...80 °C   |
| Operating altitude                    | 0...2000 m conforming to IEC 61851-22   |
| Relative humidity                     | 0...95 %  |

## Offer Sustainability

|                                  |   |
|----------------------------------|---|
| Sustainable offer status         | Green Premium product   |
| RoHS (date code: YYWW)           | Compliant - since 1306 - Schneider Electric declaration of conformity<br><a href="#">Schneider Electric declaration of conformity</a> |
| REACH                            | Reference contains SVHC above the threshold - Go to CaP for more details<br><a href="#">Go to CaP for more details</a>                |
| Product environmental profile    | Available<br><a href="#">Product Environmental Profile</a>  |
| Product end of life instructions | Available<br><a href="#">End of Life Information</a>  |