

# Product data sheet

Specifications



## EVLINK PARKING WALL MOUNTED 7KW 2XT2 with shutter RFID EV CHARGING STATION

EVW1S7P44R

⚠ Discontinued on: Jul 1, 2020

⚠ Discontinued

### Main

Range	EVlink
Product Name	EVlink parking
Product Or Component Type	Charging station
Device Short Name	EVW1
Poles Description	1P + N for control circuit 1P + N for power circuit
Mounting Mode	Wall-mounted
Offer Type	Standard
Rated Supply Voltage	230 V AC 50/60 Hz control circuit 230 V AC 50/60 Hz power circuit
Earthing System	TT TN
Socket-Outlet Number	2
Socket-Outlet Type	Right: T2 with shutter / silver plated contacts Left: T2 with shutter / silver plated contacts
Maximum Supply Current	32 A
Max Power	7 kW
Access Control System	Badge RFID

### Complementary

Control Type	2 green illuminated push-button, function: unlock flap 2 red push-button, function: stop
Local Signalling	On charge: 2 LED (green) (flashing) Available: 2 LED (green) Reserved: 2 LED (orange) Not operational: 2 LED (red)
Standards	IEC 61851-22 IEC 61851-1
Product Certifications	CE CB
Height	620 mm
Width	413 mm
Depth	256 mm
Net Weight	33 kg

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

# Environment

Ip Degree Of Protection	IP54 off load conforming to IEC 61851-1 IP54 on load conforming to IEC 61851-1
Ik Degree Of Protection	IK10 charging station conforming to IEC 61851-22 IK08 socket-outlet conforming to IEC 61851-22
Ambient Air Temperature For Operation	-30...50 °C conforming to IEC 61851-22
Ambient Air Temperature For Storage	-40...80 °C
Operating Altitude	0...2000 m conforming to IEC 61851-22
Relative Humidity	0...95 %

# Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	50 cm
Package 1 Width	45 cm
Package 1 Length	68 cm
Package 1 Weight	26.5 kg