Product data sheet

Specifications



Lisse - switched socket - lockable - 2 gangs - 13 A 230 V white

GGBL3060L

Main

Range	Lisse
Aesthetic Name	White moulded
Product Or Component Type	Switched socket
Device Presentation	Complete product
Outlet Standard	British
Colour Tint	Matt white
Quantity Per Set	Set of 5
Type Of Packing	Carton

Complementary

Switch Function	2-pole
Rated Current	13 A at 250 V AC 50 Hz
Actuator	Кеу
Number Of Gangs	2 gangs
Pilot Light	without LED
Fixing Mode	By screws
Connections - Terminals	Screw terminals
Material	Urea (carbamide)
Type Of Installation	Indoor
Depth	43.8 mm
Width	148.5 mm
Height	87 mm

Environment

Standards	BS 1363-2
Ip Degree Of Protection	IP20

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	4.400 cm
Package 1 Width	9.000 cm

Package 1 Length	15.000 cm
Package 1 Weight	228.500 g
Unit Type Of Package 2	BB1
Number Of Units In Package 2	5
Package 2 Height	9.500 cm
Package 2 Width	15.500 cm
Package 2 Length	23.000 cm
Package 2 Weight	1.240 kg
Unit Type Of Package 3	S04
Number Of Units In Package 3	50
Package 3 Height	30.000 cm
Package 3 Width	40.000 cm
Package 3 Length	60.000 cm
Package 3 Weight	13.045 kg

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



RoHS/REACh

Well-being performance

Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Circularity Profile	End of Life Information