

Lisse - Cooker Control Unit with 13A Socket LED Ind 45A DP Stainless Stl with Wh

GGBL4001WSS

Main

Range	Lisse	
Aesthetic Name	Screwless deco	
Product Or Component Type	Cooker control unit	
Device Presentation	Complete product	
Outlet Standard	British	
Colour Tint	Cover plate: brushed finish stainless steel Interior: white	
Quantity Per Set	Set of 1	

Complementary

Rated Current	45 A at 230 V AC 50 Hz
Number Of Gangs	2 gangs
Pilot Light	LED
Fixing Mode	Concealed screws M3.5 x 30 mm
Connections - Terminals	Screw terminals
Material	Stainless steel
Type Of Installation	Indoor
Depth	33 mm
Width	148 mm
Height	87 mm
Net Weight	0.286 kg

Environment

Standards	BS 4177
Ip Degree Of Protection	IP20

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	4.7 cm
Package 1 Width	9.1 cm
Package 1 Length	15.5 cm

Package 1 Weight	325.3 g
Unit Type Of Package 2	CAR
Number Of Units In Package 2	50
Package 2 Height	18 cm
Package 2 Width	48 cm
Package 2 Length	49 cm
Package 2 Weight	16.983 kg
Unit Type Of Package 3	PAM
Number Of Units In Package 3	1000
Package 3 Height	106.5 cm
Package 3 Width	100 cm
Package 3 Length	120 cm
Package 3 Weight	359.658 kg

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Rohs Exemption Information

Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations