Specifications



Lisse - Fuse connection unit - 1 gang - 13 A - white moulded

GGBL5010

Main

Range	Lisse
Aesthetic Name	White moulded
Product Or Component Type	Fuse connection unit
Device Presentation	Complete product
Colour Tint	Cover plate: white moulded
Quantity Per Set	Set of 10

Complementary

Pilot Lightwithout LEDActuatorRockerNumber Of Gangs1 gangMaterialUrea (carbamide)Device MountingWall mountedFixing ModeBy screwsRated Current13 A at 250 V ACConnections - TerminalsScrew terminalsType Of PackingCartonWidth87 mmHeight87 mmDepth28 mmNet Weight0.101 km		
Number Of Gangs1 gangMaterialUrea (carbamide)Device MountingWall mountedFixing ModeBy screwsRated Current13 A at 250 V ACConnections - TerminalsScrew terminalsType Of PackingCartonWidth87 mmHeight87 mmDepth28 mm	Pilot Light	without LED
Material Urea (carbamide) Device Mounting Wall mounted Fixing Mode By screws Rated Current 13 A at 250 V AC Connections - Terminals Screw terminals Type Of Packing Carton Width 87 mm Height 87 mm Depth 28 mm	Actuator	Rocker
Device MountingWall mountedFixing ModeBy screwsRated Current13 A at 250 V ACConnections - TerminalsScrew terminalsType Of PackingCartonWidth87 mmHeight87 mmDepth28 mm	Number Of Gangs	1 gang
Fixing Mode By screws Rated Current 13 A at 250 V AC Connections - Terminals Screw terminals Type Of Packing Carton Width 87 mm Height 87 mm Depth 28 mm	Naterial	Urea (carbamide)
Rated Current 13 A at 250 V AC Connections - Terminals Screw terminals Type Of Packing Carton Width 87 mm Height 87 mm Depth 28 mm	Device Mounting	Wall mounted
Connections - Terminals Screw terminals Type Of Packing Carton Width 87 mm Height 87 mm Depth 28 mm	ixing Mode	By screws
Type Of Packing Carton Width 87 mm Height 87 mm Depth 28 mm	Rated Current	13 A at 250 V AC
Width 87 mm Height 87 mm Depth 28 mm	Connections - Terminals	Screw terminals
Height 87 mm Depth 28 mm	ype Of Packing	Carton
Depth 28 mm	Vidth	87 mm
	leight	87 mm
Net Weight 0 101 kg	Depth	28 mm
······································	let Weight	0.101 kg

Environment

Standards	BS 1363
Ip Degree Of Protection	IP20

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	2.8 cm
Package 1 Width	8.7 cm
Package 1 Length	8.7 cm

Package 1 Weight	102.7 g
Unit Type Of Package 2	BB1
Number Of Units In Package 2	10
Package 2 Height	9.5 cm
Package 2 Width	15.5 cm
Package 2 Length	18.5 cm
Package 2 Weight	1.135 kg
Unit Type Of Package 3	CAR
Number Of Units In Package 3	100
Package 3 Height	17 cm
Package 3 Width	38.5 cm
Package 3 Length	49.5 cm
Package 3 Weight	11.884 kg

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



RoHS/REACh

Well-being performance

Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Circularity Profile	End of Life Information