Specifications



Lisse - Switched FCU - LED Indicator - 13A DP Stainless Steel with Black Interio

GGBL5011BSS

Main

Range	Lisse	
Aesthetic Name	Screwless deco	
Product Or Component Type	Fuse connection unit	
Device Presentation	Complete product	
Colour Tint	Interior: black Cover plate: stainless steel	
Quantity Per Set	Set of 10	

Complementary

Pilot Light	LED
Actuator	Rocker
Number Of Gangs	1 gang
Material	Stainless steel
Device Mounting	Wall mounted
Fixing Mode	Concealed screws
Rated Current	13 A at 250 V AC
Connections - Terminals	Screw terminals
Type Of Packing	Box
Width	87 mm
Height	87 mm
Depth	28 mm
Net Weight	0.138 kg

Environment

Standards	BS 1363
Ip Degree Of Protection	IP20

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.3 cm
Package 1 Width	9.1 cm

Package 1 Length	9.1 cm
Package 1 Weight	168.2 g
Unit Type Of Package 2	CAR
Number Of Units In Package 2	100
Package 2 Height	20 cm
Package 2 Width	36 cm
Package 2 Length	48 cm
Package 2 Weight	17.349 kg
Unit Type Of Package 3	РАМ
Number Of Units In Package 3	2400
Package 3 Height	96.5 cm
Package 3 Width	100 cm
Package 3 Length	120 cm
Package 3 Weight	436.355 kg

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Eà

 (Δ)

Transparency RoHS/REACh

Well-being performance

Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations