Specifications



# Main

Aesthetic Name	Flat plate
Product Or Component Type	Socket-outlet
Rated Current	13 A at 230 V AC 50 Hz
Fixing Mode	By screws M3.5 x 30 mm
Colour Tint	Stainless steel

GU3252WSS

Socket-outlet, Ultimate, complete product, 1P, British, stainless steel

## Complementary

oomplemental y	
Device Presentation	Complete product
Outlet Poles Configuration	1P
Outlet Standard Description	3 pins
Outlet Standard	British
Number Of Gangs	2 gangs
Earth Circuit	Standard earth
Pilot Light	Without neon indicator
Device Mounting	Wall mounted
Connections - Terminals	Screw terminal
Material	Steel
Quantity Per Set	Set of 1
Height	88 mm
Width	148 mm
Depth	27 mm

### Environment

Ip Degree Of Protection	IP20
Standards	BS 1363

## **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	4.000 cm
Package 1 Width	11.600 cm
Package 1 Length	15.300 cm

Package 1 Weight	463.300 g
Unit Type Of Package 2	CAR
Number Of Units In Package 2	40
Package 2 Height	18.000 cm
Package 2 Width	40.700 cm
Package 2 Length	48.000 cm
Package 2 Weight	19.065 kg
Unit Type Of Package 3	РАМ
Number Of Units In Package 3	800
Package 3 Height	106.500 cm
Package 3 Width	120.000 cm
Package 3 Length	100.000 cm
Package 3 Weight	401.292 kg

## **Contractual warranty**

Warranty

18 months

#### **Sustainability**

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

#### Well-being performance

Rohs Exemption Information	Yes
Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration