

Current limiter, TeSys Deca Frame 2,32A/690V, activation 1.5kA, at top of GV2ME/GV2P/GV2RT with screw clamp connections

GV1L3

### Main

Range	TeSys	
Range Of Product	TeSys GV2	
	TeSys Deca	
Accessory / Separate Part Category	Protection accessory	
Product Or Component Type	Current limiting module	
Range Compatibility	TeSys GV2	
	TeSys Deca	
Product Compatibility	GV2RT	
	GV2ME	
	GV2P	
	GV2L	
Function Of Module	Increasing the breaking capacity of a circuit breaker	
Mounting Location	On top of the circuit breaker	
[le] Rated Operational Current	32 A	
[Ith] Conventional Free Air Thermal Current	63 A conforming to IEC 60947-1	
Activation Threshold	1500 A	
Breaking Capacity	<= 100 kA depending on protective device	
[Ue] Rated Operational Voltage	690 V AC 50/60 Hz	
[Ui] Rated Insulation Voltage	690 V AC 50/60 Hz conforming to IEC 60947-1	

## Complementary

Connections - Terminals	Screw clamp terminals $1 \times 1.525 \text{ mm}^2$ rigid Screw clamp terminals $2 \times 1.510 \text{ mm}^2$ rigid Screw clamp terminals $1 \times 1.525 \text{ mm}^2$ flexible without cable end Screw clamp terminals $2 \times 1.510 \text{ mm}^2$ flexible without cable end Screw clamp terminals $1 \times 1.516 \text{ mm}^2$ flexible with cable end Screw clamp terminals $2 \times 1.54 \text{ mm}^2$ flexible with cable end
Tightening Torque	2.2 N.m
Net Weight	0.13 kg

# **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	8.5 cm
Package 1 Width	5.0 cm
Package 1 Length	8.0 cm

Package 1 Weight	122.0 g
Unit Type Of Package 2	S01
Number Of Units In Package 2	24
Package 2 Height	15.0 cm
Package 2 Width	15.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	3.104 kg

## **Sustainability**

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance

Reach Free Of Svhc

Toxic Heavy Metal Free

Mercury Free

Rohs Exemption Information
Yes

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
	Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information
California Proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Connections and Schema

**Current Limiter** 

