Product data sheet

Specifications



integrated servo motor - 4.4 Nm - 3000 rpm - keyed shaft - without brake

ILM1002P11A0000

Main

| Range Of Product | PacDrive 3 |
|---------------------------|------------------------------|
| Product Or Component Type | Servo motor integrated drive |
| Device Short Name | ILM |

Complementary

| Complementary | |
|---------------------------|--|
| [Us] Rated Supply Voltage | 250700 V |
| Continuous Stall Current | 2.9 A |
| Continuous Stall Torque | 4.4 N.m |
| Peak Stall Torque | 18.3 N.m |
| Nominal Output Power | 910 W |
| Nominal Torque | 2.9 N.m |
| Nominal Speed | 3000 rpm |
| Maximum Current Irms | 13.1 A |
| [In] Rated Current | 2 A |
| Shaft End | Keyed |
| Second Shaft | Without second shaft end |
| Shaft Diameter | 19 mm |
| Shaft Length | 40 mm |
| Key Width | 30 mm |
| Feedback Type | Absolute single turn SinCos Hiperface |
| Speed Feedback Resolution | 128 periods |
| Holding Brake | Without |
| Mounting Support | International standard flange |
| Motor Flange Size | 100 mm |
| Torque Constant | 1.52 N.m/A at 120 °C |
| Back Emf Constant | 100 V/krpm at 20 °C |
| Number Of Motor Poles | 8 |
| Rotor Inertia | 2.31 kg.cm ² |
| Stator Resistance | 4.12 Ohm at 20 °C for Ph/Ph 2.86 Ohm at 120 °C for Ph/N |
| Stator Inductance | 21.8 mH at 20 °C for Ph/Ph 10.9 mH at 120 °C for Ph/N |

| Maximum Radial Force Fr | 990 N at 1000 rpm 790 N at 2000 rpm 690 N at 3000 rpm |
|--|---|
| Maximum Axial Force Fa | 0.2 x Fr |
| Type Of Cooling | Natural convection |
| Length | 249 mm |
| Number Of Motor Stacks | 2 |
| Centring Collar Diameter | 95 mm |
| Centring Collar Depth | 3.5 mm |
| Number Of Mounting Holes | 4 |
| Mounting Holes Diameter | 9 mm |
| Circle Diameter Of The Mounting Holes | 115 mm |
| Net Weight | 6.4 kg |

Environment

Ip Degree Of Protection

IP54

Packing Units

| U | |
|------------------------------|---------|
| Unit Type Of Package 1 | PCE |
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 26.0 cm |
| Package 1 Width | 20.0 cm |
| Package 1 Length | 59.0 cm |
| Package 1 Weight | 7.23 kg |

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Eq

Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc
Mercury Free
Rohs Exemption Information Yes
Pvc Free

Certifications & Standards

| Reach Regulation | REACh Declaration |
|---------------------------|---|
| Eu Rohs Directive | Pro-active compliance (Product out of EU RoHS legal scope) |
| China Rohs Regulation | China RoHS declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End of Life Information |
| California Proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |