
Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications





ISM20550P

! Discontinued on: Sep 30, 2022

① Discontinued

Main

Cabling Installation System	Pole
Product Or Component Type	Ceiling frame

Complementary

Type Of Pole	One-sided
Colour Tint	Polar white (RAL 9003)
Quantity Per Set	Set of 1
Product Compatibility	Unica wiring device
Pole/Post Surface Finish	Anodized Powder coated
Pole Fixing Mode	Tension-mounted
Fixing Mode	Self-sticking
Material	PS (polystyrene)
Length	170 mm
Height	1 mm
Width	111 mm

Environment

Ambient Air Temperature For Operation	-25…60 °C
Ip Degree Of Protection	IP40

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	0.1 cm
Package 1 Width	11.1 cm
Package 1 Length	17.0 cm
Package 1 Weight	13.0 g
Unit Type Of Package 2	BAG
Number Of Units In Package 2	1
Package 2 Height	0.1 cm

Package 2 Width	15.0 cm
Package 2 Length	20.0 cm
Package 2 Weight	13.0 g
Unit Type Of Package 3	S02
Number Of Units In Package 3	100
Package 3 Height	15.0 cm
Package 3 Width	30.0 cm
Package 3 Length	40.0 cm
Package 3 Weight	1.6 kg

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance

Toxic Heavy Metal Free	
Mercury Free	
Rohs Exemption Information	Yes
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
	Pro-active China RoHS declaration (out of China RoHS legal scope)