

# OptiLine 45/50 - floor feeder adaptor - polar white

ISM20826P

! Discontinued on: Jun 30, 2023

#### (!) Discontinued

#### Main

Cabling Installation System	Post Pole
Product Or Component Type	Adaptor

## Complementary

Type Of Pole	One-sided One installation box Two installation boxes	
Type Of Post	One-sided Two-sided	
Colour Tint	Polar white (RAL 9003)	
Quantity Per Set	Set of 1	
Pole/Post Surface Finish	Powder coated	
Pole Fixing Mode	Tension-mounted	
Material	PC/ABS	
Length	110 mm	
Height	60 mm	
Width	63 mm	

#### **Environment**

Standards	EN 50085-1:2005 NF C 68-102
Ambient Air Temperature For Operation	-2560 °C
Ip Degree Of Protection	IP40

## **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	4.0 cm
Package 1 Width	17.0 cm
Package 1 Length	17.0 cm
Package 1 Weight	52.0 g
Unit Type Of Package 2	S03

Number Of Units In Package 2	50
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	3.09 kg

### **Sustainability**

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance



Reach Free Of Svhc



Rohs Exemption Information

Yes

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration  Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations