Specifications



End feed unit, Canalis KBA, 25A, left mounting, 1 circuit, compatible DALI, white RAL9003

KBA25ABG4W

#### Main

Range Of Product	Canalis
Device Short Name	КВА
Product Compatibility	Canalis KBA busbar trunking 25 A
Offer Type	Classic Control system
Product Or Component Type	Feed unit
Conductors Material	Aluminium
[Ie] Rated Operational Current	25 A
[Ue] Rated Operational Voltage	230400 V
Number Of Circuits	1
Busbar Trunking Polarity	3L + N + PE L + N + PE
Protection Type	Without protection
Control Type	Communicating
Communication Port Protocol	DALI
Colour	White (RAL 9003)

# Complementary

Provided Equipment	End cover
Mounting Location	Left
Mounting Mode	By screws
Mounting Support	Busbar
Connections - Terminals	Terminal block - Pg 16 - screw clamp connector for 4 mm <sup>2</sup>
Width	273 mm
Depth	57 mm
Height	57 mm
Net Weight	200 g
Standards	IEC 61439-6

### Environment

Ip Degree Of Protection

IP55 conforming to IEC 60529

# **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	5.5 cm
Package 1 Width	5.5 cm
Package 1 Length	29.0 cm
Package 1 Weight	216.0 g
Unit Type Of Package 2	S03
Number Of Units In Package 2	24
Package 2 Height	30 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	5.8 kg
Unit Type Of Package 3	P06
Number Of Units In Package 3	192
Package 3 Height	75 cm
Package 3 Width	60 cm
Package 3 Length	80 cm
Package 3 Weight	54 kg

# **Contractual warranty**

Warranty

18 months

### Sustainability

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Eq

### Well-being performance

Reach Free Of Svhc
Toxic Heavy Metal Free
Mercury Free
Rohs Exemption Information Yes
Halogen Free Product

### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations

# Product data sheet

**Dimension Drawings** 



