

Canalis - distribution flexible length - 20 A - 23 m - 1.35 m between tap-offs

KDP20ED423135

! Discontinued

Main

Range Of Product	Canalis
Product Or Component Type	Busbar trunking
Product Compatibility	KDP
Busbar Description	Flexible bar

Complementary

Device Application	Power socket distribution Lighting
[Ue] Rated Operational Voltage	230400 V
[Uimp] Rated Impulse Withstand Voltage	4 kV
[Ui] Rated Insulation Voltage	690 V
[le] Rated Operational Current	20 A at 35 °C
[Icw] Rated Short-Time Withstand Current	0.34 kA
[lpk] Rated Peak Withstand Current	3.6 kA
Network Frequency	50/60 Hz
Maximum Radiated Magnetic Field	2 pT
Thdi	015 % 20 A 1533 % 16 A 33100 % 14 A
Maximum Voltage Drop	<0.72 V with power factor = 1 at 50 Hz with 1A for 100 m long <0.65 V with power factor = 0.9 at 50 Hz with 1A for 100 m long <0.58 V with power factor = 0.8 at 50 Hz with 1A for 100 m long <0.5 V with power factor = 0.7 at 50 Hz with 1A for 100 m long
Busbar Trunking Polarity	L2 + L1 + L3 + N + PE
Tap-Off Unit Interval	1350 mm
Type Of Packing	Spool
Standards	EN/IEC 60439-2 EN/IEC 61439-6
Length	23 m
Net Weight	7.36 kg

Environment

Ip Degree Of Protection IP55 conforming to IEC 60529

Ik Degree Of Protection	IK07 conforming to IEC 62262
Ambient Air Temperature For Operation	3540 °C (93 % of In) 4045 °C (85 % of In) 4550 °C (76 % of In) 5055 °C (66 % of In) 035 °C (100 % of In)

Contractual warranty

Warranty 18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Eu Rohs Directive

Pro-active compliance (Product out of EU RoHS legal scope)

EU RoHS Declaration