

Product data sheet

Specifications



Copper flexible link, Canalys KR, connection accessory, silvered copper, made to measure length, cross section 500mm²

KRB0100YC205S

Main

Range	Canalis
Product Name	KR
Product Or Component Type	Flexible link
Device Short Name	KRB
Range Compatibility	Canalis KR
Accessory / Separate Part Category	Connection accessory
Material	Silver plated copper
Length	310...500 mm

Complementary

Bolt Diameter	M12
Mounting Mode	Bolt-on
Thickness	5 mm
Nominal Cross Section	500 mm ²
Width	110 mm
Net Weight	2.2 kg
Quantity Per Set	Set of 1

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	5.0 cm
Package 1 Width	10.0 cm
Package 1 Length	50.0 cm
Package 1 Weight	2.31 kg

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

✓ Reach Free Of Svhc

✓ Toxic Heavy Metal Free

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

✓ Halogen Free Plastic Parts Product

Certifications & Standards

Reach Regulation	REACH Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information