Specifications



End feed unit, Canalis KSA1000, aluminium, 800/1000A, right mounting, without line protection, 3L+N+PE, white RAL9001

KSA1000ABD4

#### Main

| Range Of Product               | Canalis                               |
|--------------------------------|---------------------------------------|
| Product Name                   | KS                                    |
| Device Short Name              | KSA                                   |
| Product Compatibility          | Canalis KSA busbar trunking 5001000 A |
| Offer Type                     | Classic<br>Rising main                |
| Product Or Component Type      | Feed unit                             |
| Conductors Material            | Aluminium                             |
| [le] Rated Operational Current | 1000 A                                |
| [Ue] Rated Operational Voltage | 230690 V                              |
| Number Of Circuits             | 1                                     |
| Busbar Trunking Polarity       | 3L + N + PE                           |
| Protection Type                | Without protection                    |
| Control Type                   | Without                               |
| Colour                         | White (RAL 9001)                      |

# Complementary

| Provided Equipment      | End cover   |
|-------------------------|---|
| Mounting Location       | Right<br>Left                                     |
| Mounting Mode           | By screws   |
| Mounting Support        | Busbar  |
| Body Material           | Metal   |
| Connections - Terminals | Lug for 240 mm² flexible<br>Lug for 300 mm² rigid |
| Width                   | 753 mm  |
| Depth                   | 370 mm  |
| Height                  | 457 mm  |
| Net Weight              | 25 kg   |
| Standards               | IEC 61439-1<br>IEC 61439-6                        |

Disclaimer. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| Ip Degree Of Protection | IP55 conforming to IEC 60529 |  |
|-------------------------|------------------------------|--|
| Ik Degree Of Protection | IK08 conforming to IEC 62262 |  |

# **Packing Units**

| Unit Type Of Package 1       | PCE       |
|------------------------------|-----------|
| Number Of Units In Package 1 | 1         |
| Package 1 Height             | 40.500 cm |
| Package 1 Width              | 53.000 cm |
| Package 1 Length             | 78.000 cm |
| Package 1 Weight             | 30.600 kg |

# **Contractual warranty**

Warranty

18 months

### Sustainability

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Eq

#### Well-being performance

Reach Free Of Svhc
Toxic Heavy Metal Free
Mercury Free
Rohs Exemption Information Yes
Halogen Free Product

### **Certifications & Standards**

| Reach Regulation         | REACh Declaration   |
|--------------------------|---|
| Eu Rohs Directive        | Compliant<br>EU RoHS Declaration  |
| China Rohs Regulation    | China RoHS declaration<br>Pro-active China RoHS declaration (out of China RoHS legal scope)                                 |
| Environmental Disclosure | Product Environmental Profile   |
| Weee                     | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Circularity Profile      | No need of specific recycling operations  |

## Product data sheet

**Dimensions Drawings** 

#### Dimensions

