Specifications



Tap off unit, Canalis KS 500A to 1000A, for switch disconnector FuPacT ISFT, 400A, 3L+PEN, IP55, RAL9001

KSB400HD502

Main

Range Of Product	Canalis
Range Compatibility	Canalis KS busbar trunking
Product Or Component Type	Tap-off unit
Busbar Trunking Compatibility	Canalis KS busbar trunkingplug-in
[le] Rated Operational Current	400 A at 35 °C
Protection Type	FuPacT ISFT switch-disconnector fuse: DIN fuse, size NH2
Provided Equipment	fuse
Mounting Mode	Plug-in with auto-clamping system
Colour	White (RAL 9001)

Complementary

Device Application	High power distribution
[Ue] Rated Operational Voltage	500 V
[Ui] Rated Insulation Voltage	500 V
Electrical Connection	Cable gland - ISO63 (x2)
Standards	IEC 61439-1 IEC 61439-6
Body Material	Metal

Environment

Ip Degree Of Protection	IP20 conforming to IEC 60529
Ik Degree Of Protection	IK08 conforming to IEC 62262

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	38.000 cm
Package 1 Width	46.000 cm
Package 1 Length	75.000 cm
Package 1 Weight	24.430 kg

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance



Eà

Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations