

Sprinkler proofing kit, Canalis KSA 100A to 400A, aluminium, IP55, white RAL9001

KSB400ZB2

Main

Range Of Product	Canalis	
Product Name	KS	
Product Or Component Type	Sprinkler proofing device	
Product Compatibility	KS	
[le] Rated Operational Current	160 A 250 A 400 A 100 A	
Offer Type	Spare part	
Colour	White (RAL 9001)	

Complementary

Device Application	Medium power distribution
[Ue] Rated Operational Voltage	230690 V
Control Type	Without
Number Of Circuits	1
Width	211 mm
Depth	85 mm
Height	185 mm
Net Weight	1 kg

Environment

Ik Degree Of Protection	IK08 conforming to IEC 62262
Ip Degree Of Protection	IP55 conforming to IEC 60529
Standards	IEC 60439-2 IEC 61439-6

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	12.700 cm
Package 1 Width	19.600 cm
Package 1 Length	22.500 cm
Package 1 Weight	1.480 kg

Unit Type Of Package 2	P06
Number Of Units In Package 2	30
Package 2 Height	64.000 cm
Package 2 Width	60.000 cm
Package 2 Length	80.000 cm
Package 2 Weight	58.000 kg

Contractual warranty

Warranty 18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

②	Reach Free Of Svhc	
Ø	Toxic Heavy Metal Free	
Ø	Mercury Free	
Ø	Rohs Exemption Information	Yes
⊘	Halogen Free Product	

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations