

Canalis - Cu length for plug-in tapoff unit - 1600A - 3L+PE - 2m standard

KTC1600ED320

① Discontinued

Main

Range	Canalis
Product Name	КТ
Product Or Component Type	Busbar trunking
Busbar Description	Distribution length
Device Short Name	KTC
Device Application	High power distribution
Material	Copper
[le] Rated Operational Current	1600 A at 35 °C
Polarity	3L + PE
Number Of Tap-Off Outlets	3
Nominal Output Current	25630 A
Earth Conductor	Standard earth
Short-Circuit Level	Standard version
Length	2000 mm
Provided Equipment	Trunking unit Jointing unit

Complementary

Housing Material	Polyester film
Contacts Material	Copper
[Ue] Rated Operational Voltage	1000 V
Network Frequency	50/60 Hz
[Ui] Rated Insulation Voltage	1000 V
[Icw] Rated Short-Time Withstand Current	65 kA
[lpk] Rated Peak Withstand Current	143 kA
Electrical Connection	Sliding contact
Radiated Magnetic Field	0.75 μΤ
Thermal Stress Limit	4225000 kA².s
Thdi	015 % 1600 A 1533 % 1350 A 33100 % 1000 A

Maximum Voltage Drop	<0.0027 V with power factor = 0.7 at 50 Hz with 1A for 100 m long <0.0026 V with power factor = 1 at 50 Hz with 1A for 100 m long <0.0029 V with power factor = 0.9 at 50 Hz with 1A for 100 m long <0.0028 V with power factor = 0.8 at 50 Hz with 1A for 100 m long	
Mounting Mode	By hook	
Mounting Support	Pendant Cantilever arm	
Installation Direction	Vertical Horizontal	
Neutral Position	Right	
Tap-Off Unit Interval	500 mm	
Standards	IEC 61439-6 IEC 61439-1	
Dimension Type	Fix	
Width	140 mm	
Height	124 mm	
Colour	White (RAL 9001)	
Net Weight	58 kg	
Linear Load	29 kg/m	

Environment

Ip Degree Of Protection	IP55 conforming to IEC 60529
Ik Degree Of Protection	IK08 conforming to IEC 62262
Derating Factor	035 °C (100 % of In) 3540 °C (95 % of In) 4045 °C (90 % of In) 4550 °C (84 % of In) 5055 °C (79 % of In)

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1