

C-Bus-3 channel 5A architectural dimmer-without RCD-universal

L5103D5UA

Main

Range	C-Bus
Product Or Component Type	Dimmer
Device Application	Control
Load Type	Incandescent: 20 W (minimum)
Provided Equipment	RCCB, 4
Number Of Channels	3

Complementary

Maximum Leakage Current	10 mA
[Us] Rated Supply Voltage	240 V AC 4753 Hz 415 V AC 4753 Hz
Starting Time	0.5 s
Rated Breaking Capacity	6 kA
[Ui] Rated Insulation Voltage	500 V
Net Weight	9.5 kg
Width	412 mm
Height	289 mm
Depth	164 mm

Environment

Dielectric Strength	2500 V
Directives	2004/108/EC - electromagnetic compatibility
Standards	EN 61000-3-2 AS/NZS CISPR 14-1 EN 61000-3-5 AS/NZS 3439-1 EN 55014-1 EN 61000-3-11 IEC 60439-1 EN 61000-3-3 EN 55015 AS/NZS CISPR 15 IEC 60669-2-1

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1

Package 1 Height	61.8 cm
Package 1 Width	29.4 cm
Package 1 Length	37.0 cm
Package 1 Weight	13.76 kg

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

Toxic Heavy Metal Free

Mercury Free

Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation

Eu Rohs Directive

Compliant
EU RoHS Declaration

China Rohs Regulation

China RohS declaration
Pro-active China RoHS declaration (out of China RoHS legal scope)

Environmental Disclosure

Product Environmental Profile

Circularity Profile

End of Life Information